

S3X 125 1000V R 80 Im= 800 3p F F



S3X 125 1000V R 80 Im= 800 3p F F

General Information

Extended Product Type	S3X 125 1000V R 80 Im= 800 3p F F
Product ID	1SDA050453R1
EAN	8015644506070
Catalog Description	S3X 125 1000V R 80 Im= 800 3p F F
Long Description	CURRENT-LIMITING C.BREAKER ISOMAX S3X 125 1000V THREE-POLE FIXED WITH FRONT TERMINALS AND PROTECTIVE RELEASES THERMOMAGNETIC IN AC R 80-800 A

Ordering

EAN	8015644506070
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	178 mm
Product Net Height	233 mm
Product Net Length	200 mm
Product Net Depth / Length	0.1035 m
Product Net Weight	3.6 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	233 mm
Package Level 1 Depth / Length	178 mm
Package Level 1 Gross Weight	6.6 kg
Package Level 1 EAN	8015644506070

Additional Information

Electrical Durability	10000
Number of Poles	3
Power Loss	30.8 W
Product Main Type	SACE Isomax
Product Name	Moulded Case Circuit Breaker

Rated Current (I_n)	125 A
Rated Operational Voltage	690 V AC
Release Type	TadjM10
Standards	IEC947-2
Sub-type	S3
Suitable For	Isomax S3
Suitable for Product Class	Isomax
Terminal Connection Type	Front
Test Voltage at Industrial Frequency for 1 Minute	3000 V
Version	Fixed

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	ITSCE-604050012
Declaration of Conformity - CE	1SDL000160R0021
Environmental Information	1SDL000141R0
Instructions and Manuals	ITSCE-605071013
RoHS Information	1SDL000199R0001

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
Object Classification Code	Q

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Isomax

Low Voltage Products and Systems → Circuit Breakers → Service → Replacements

