

SKT250-220X-100



UV BLACK TIE 220N 250MM DISTRI PACK



General Information

Extended Product Type	SKT250-220X-100
Product ID	7TCA300220R0002
EAN	5415022210309
Catalog Description	UV BLACK TIE 220N 250MM DISTRI PACK
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 250mm (9.842 Inches), Width of 4.8mm (0.189 Inch), Thickness of 1.3mm (0.051 Inch), Bundle Diameter 3.0mm (0.118 Inch) to 60mm (2.36 Inches), Tensile Strength Rating of 220 Newtons (50 Pounds)
Lock Type	Plastic Pawl

Ordering

EAN	5415022210309
Minimum Order Quantity	6000 piece
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	1.814 g
--------------------	---------

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	130.048 mm
Package Level 1 Height	70.104 mm
Package Level 1 Depth / Length	370.078 mm
Package Level 2 Units	12000 piece
Package Level 2 Width	379.984 mm
Package Level 2 Height	359.918 mm
Package Level 2 Depth / Length	569.976 mm

Additional Information

Brand / Label	Spec-Kon
Color	Black
Function	For Temperatures up to 85 Degrees Celsius (185 F). Weather and Ultraviolet Resistant for Indoor and Outdoor Applications. The right cable tie for control panels and wiring harness applications.

Material	Nylon/Polyamide 6.6
Product Main Type	GENERAL PURPOSE CABLE TIES AND ACCESSORIES
Product Name	OTHER PLASTIC ITEM
Product Type	Standard
Special Functions	Cost effective and easy to install
Standards	UL E49405
UPC	753554016576

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SKT250-220X-100
Instructions and Manuals	SKT250-220X-100

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

