

SKT250-220X



UV BLACK TIE 220N 250MM OEM PACK



General Information

Extended Product Type	SKT250-220X
Product ID	7TCA300240R0002
EAN	5415022210316
Catalog Description	UV BLACK TIE 220N 250MM OEM PACK
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 250mm (9.842 Inches), Width of 4.8mm (0.189 Inches), Thickness of 1.3mm (0.051 Inches), Tensile Strength Rating of 220 Newtons (50 Pounds), Bulk Pack
Lock Type	Plastic Pawl

Ordering

EAN	5415022210316
Minimum Order Quantity	6000 piece
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	1.814 g
--------------------	---------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	350.012 mm
Package Level 1 Height	70.104 mm
Package Level 1 Depth / Length	430.022 mm
Package Level 2 Units	12000 piece
Package Level 2 Width	379.984 mm
Package Level 2 Height	359.918 mm
Package Level 2 Depth / Length	569.976 mm

Additional Information

Brand / Label	Spec-Kon
Color	Black
Function	For Temperatures up to 85 Degrees Celsius (185 F). Weather and Ultraviolet Resistant for Indoor and Outdoor Applications. The right cable tie for control panels and wiring harness applications.

Material	Nylon/Polyamide 6.6
Product Main Type	GENERAL PURPOSE CABLE TIES AND ACCESSORIES
Product Name	OTHER PLASTIC ITEM
Product Type	Standard
Special Functions	Cost effective and easy to install
Standards	UL E49405
UPC	753554016583

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SKT250-220X
Instructions and Manuals	SKT250-220X

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

