

SPL32/25M



25M X SPL32/BLACK CONDUIT

General Information

Extended Product Type	SPL32/25M
Product ID	7TCA296030R0238
EAN	5020963000577
Catalog Description	25M X SPL32/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963000577
Minimum Order Quantity	1 piece
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	16.497 kg
--------------------	-----------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	457.2 mm
Package Level 1 Height	355.6 mm
Package Level 1 Depth / Length	457.2 mm
Package Level 2 Units	10 piece
Package Level 2 Width	1016 mm
Package Level 2 Height	1270 mm
Package Level 2 Depth / Length	1219.2 mm

Additional Information

Brand / Label	Adaptaflex
Color	Black
Function	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Material	Galvanized Steel Core with PVC Covering
Product Main Type	ADAPTAFLEX FLEXIBLE CABLE PROTECTION

Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL32/25M
Instructions and Manuals	SPL32/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

