

TYC28MX



CABLE TIE 35LB 14IN UV BLK NYLON 12



General Information

Extended Product Type	TYC28MX
Product ID	7TCG009580R0004
EAN	5414363067207
Catalog Description	CABLE TIE 35LB 14IN UV BLK NYLON 12
Long Description	Cable Tie, Black Polyamide (Nylon 12) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 358.65mm (14.12 Inches), Width of 4.65mm (0.183 Inch), Thickness of 1.17mm (0.046 Inch), Tensile Strength Rating of 200 Newtons (50 Pounds), Bulk Pack
Lock Type	Stainless Steel Barb

Ordering

EAN	5414363067207
Minimum Order Quantity	1000 piece
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	2.268 g
--------------------	---------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	355.6 mm
Package Level 1 Height	508.001 mm
Package Level 1 Depth / Length	508 mm
Package Level 1 EAN	00786210848020
Package Level 2 Units	5000 piece
Package Level 2 Width	259.08 mm
Package Level 2 Height	350.52 mm
Package Level 2 Depth / Length	500.38 mm
Package Level 2 EAN	50786210848025

Additional Information

Brand / Label	Ty-Rap
---------------	--------

Color	Black
Material	Nylon/Polyamide 6.6
Order Multiple	1000 piece
Product Main Type	PERFORMANCE CABLE TIES AND ACCESSORIES
Product Name	CABLE TIES
Product Type	Standard
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
UPC	786210848020

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TYC28MX
Instructions and Manuals	TYC28MX

Classifications

E-nummer	1518235
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

