



PRODUCT-DETAILS

XLP2

XLP2 Fuse Switch Disconnecter



| General Information | |
|-----------------------|---|
| Extended Product Type | XLP2 |
| Product ID | 1SEP101892R0001 |
| EAN | 7025840016861 |
| Catalog Description | XLP2 Fuse Switch Disconnecter |
| Long Description | XLP2,3-pole,400A, without clamps or bolts |

| Circular Value | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| RoHS Information | 1SCC011020D0201 |

| Ordering | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

| | |
|-------------------|-----------------------------|
| Country of Origin | Bulgaria (BG) China (CN) |
|-------------------|-----------------------------|

Popular Downloads

| | |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SEC312012D0201 |
| Instructions and Manuals | No Instructions and Manuals needed |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width | 210 mm |
| Product Net Height | 290 mm |
| Product Net Depth / Length | 130 mm |
| Product Net Weight | 2.3 kg |

Technical

| | |
|--|--------------------------------|
| Rated Operational Current AC-21B (I _e) | (690 V) 315 A |
| Rated Operational Current AC-22B (I _e) | (500 V) 400 A (800 V) 400 A |
| Rated Impulse Withstand Voltage (U _{imp}) | Main Circuit 8 kV |
| Rated Operational Voltage | 500 V AC 690 V AC |
| Rated Frequency (f) | Main Circuit 50/60 Hz |
| Rated Conditional Short-Circuit Current (I _{nc}) | (690 V) 50 kiloampere rms |
| Power Loss | at Rated Load 13 W |
| Handle Type | Front cover 3P |
| Fuse Size | NH2 |
| Fuse System | DIN |
| Standards | IEC60947-3 GB/T14048.3 |
| Special Functions | Not Included |
| Mounting Type | Baseplate |
| Number of Poles | 3 |
| Degree of Protection | IP30 |
| Terminal Type | Lug terminals |
| Device Type Manager (DTM) | Fuseswitchdisconnector |
| Rated Current (I _n) | 400 A |
| Rated Voltage (U _r) | 500 V AC 690 V AC |
| Electronic Fuse Monitoring | No |

Environmental

| | |
|-------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SEP500050P0001 |
| REACH Declaration | 1SCC011021D0201 |

Container Information

| | |
|--------------------------------|---------------------|
| Package Level 1 Units | shrink-wrap 1 piece |
| Package Level 1 Width | 210 mm |
| Package Level 1 Depth / Length | 130 mm |
| Package Level 1 Height | 290 mm |
| Package Level 1 Gross Weight | 2.5 kg |
| Package Level 1 EAN | 7025840016861 |
| Package Level 2 EAN | 7025840016861 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | S |
| ETIM 7 | EC001040 - Fuse switch disconnectors |
| ETIM 8 | EC001040 - Fuse switch disconnectors |
| ETIM 9 | EC001040 - Fuse switch disconnectors |
| eClass | V11.1 : 27371401 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Sweden) | 3171956 |

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

