

PRODUCT-DETAILS

## XLP2-A60/120-B-below

## XLP2-A60/120-B-below Fuse Switch Disconnector



| General Information   |  |
|-----------------------|--|
| Extended Product Type | XLP2-A60/120-B-below   |
| Product ID            | 1SEP102286R0001  |
| EAN                   | 7025840081104  |
| Catalog Description   | XLP2-A60/120-B-below Fuse Switch Disconnector                                |
| Long Description      | XLP2,3-pole,400A, incl. A60/120 adapter, cable below without clamps or bolts |

| Circular Value                              |                 |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration                           | 1SCC011021D0201 |
| RoHS Information                            | 1SCC011020D0201 |

| Ordering               |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85389099 |

XLP2-A60/120-B-below 2/3

Country of Origin China (CN)

| Popular Downloads                    |                                    |
|--------------------------------------|------------------------------------|
| Data Sheet, Technical<br>Information | 1SEC312012D0201                    |
| Instructions and                     | No Instructions and Manuals needed |

| Dimensions                 |        |
|----------------------------|--------|
| Product Net Width          | 210 mm |
| Product Net Height         | 290 mm |
| Product Net Depth / Length | 210 mm |
| Product Net Weight         | 4.6 kg |

| Technical  |                           |
|--|---------------------------|
| Rated Operational<br>Current AC-21B (I <sub>e</sub> )          | (690 V) 315 A             |
| Rated Operational<br>Current AC-22B (I <sub>e</sub> )          | (500 V) 400 A             |
| Rated Impulse<br>Withstand Voltage (U <sub>imp</sub><br>)      | Main Circuit 8 kV         |
| Rated Operational<br>Voltage                                   | 500 V AC<br>690 V AC      |
| Rated Frequency (f)  | Main Circuit 50/60 Hz     |
| Rated Conditional Short-<br>Circuit Current (I <sub>nc</sub> ) | (690 V) 50 kiloampere rms |
| Power Loss   | at Rated Load 13 W        |
| Handle Type  | Front cover 3P            |
| Fuse Size  | NH2                       |
| Fuse System  | DIN                       |
| Standards  | IEC60947-3<br>GB/T14048.3 |
| Special Functions  | Not Included              |
| Mounting Type  | 60mm Busbar System        |
| Number of Poles  | 3                         |
| Degree of Protection   | IP30                      |
| Terminal Type  | Lug terminals             |
| Device Type Manager<br>(DTM)                                   | Fuseswitchdisconnector    |
| Rated Current (In)   | 400 A                     |
| Rated Voltage (Ur)   | 500 V AC<br>690 V AC      |
| Electronic Fuse<br>Monitoring                                  | No                        |

| Environmental |  |
|---------------|--|
| RoHS Status   | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

| Certificates and Declarations     |                 |
|-----------------------------------|-----------------|
| Declaration of<br>Conformity - CE | 1SEP500050P0001 |
| REACH Declaration                 | 1SCC011021D0201 |

| Container Information             |                     |
|-----------------------------------|---------------------|
| Package Level 1 Units             | shrink-wrap 1 piece |
| Package Level 1 Width             | 210 mm              |
| Package Level 1 Depth /<br>Length | 210 mm              |
| Package Level 1 Height            | 290 mm              |
| Package Level 1 Gross<br>Weight   | 4.6 kg              |
| Package Level 1 EAN               | 7025840081104       |
| Package Level 2 EAN               | 7025840081104       |

| Classifications               |  |
|-------------------------------|--|
| Object Classification<br>Code | S  |
| ETIM 7                        | EC001040 - Fuse switch disconnector                        |
| ETIM 8                        | EC001040 - Fuse switch disconnector                        |
| ETIM 9                        | EC001040 - Fuse switch disconnector                        |
| eClass                        | V11.1 : 27371401   |
| WEEE Category                 | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland)            | 3601068  |

## Categories

 $\textbf{Low Voltage Products and Systems} \rightarrow \textbf{Fusegear} \rightarrow \textbf{Fuse Switch Disconnectors} \rightarrow \textbf{EasyLine}$ 

