



PRODUCT-DETAILS

MREBC20AC2

MREBC20AC2 Timer 24 ... 250 V - Screw Terminals



General Information	
Extended Product Type	MREBC20AC2
Product ID	1SAL100542R9906
EAN	4013614550508
Catalog Description	MREBC20AC2 Timer 24 ... 250 V - Screw Terminals
Long Description	The MREBC20AC2 is an electronic timer with an adjustable drop-out between 0.2 - 24s and available for a wide control voltage range of 24...250 V AC/DC
	Electronic timers are used for realizing timing function and a compact solution in cabinet compared to separate timers
	The MREBC20AC2 electronic timers are front-mounted and locked on all MC1 and MC2 contactors or MCR contactor relays.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389091

Popular Downloads

Instructions and Manuals	2CDC102077M9901
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	35 mm
Product Net Height	21 mm
Product Net Depth / Length	36 mm
Product Net Weight	0.04 kg

Technical

Rated Operational Voltage	24 ... 250 V AC/DC
Rated Frequency (f)	50 / 60 Hz DC
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Insulation Voltage (U _i)	750 V
Degree of Protection	IP20
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Rated Control Circuit Voltage (U _c)	24 ... 250 V
Product Name	Timer
Suitable For	MC1 MC2 MCR
Suitable for Product Class	Mini Contactors

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -55 ... +80 °C
Maximum Operating Altitude Permissible	3000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
Declaration of Conformity - CE	1SAD101100-3202
Declaration of Conformity - UKCA	1SAD201100-3202
UL Certificate	E48139-19930108

Container Information	
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	25 mm
Package Level 1 Height	100 mm
Package Level 1 Gross Weight	0.045 kg
Package Level 1 EAN	4013614550508
Package Level 1 Units	bag 1 piece
Package Level 2 Width	100 mm
Package Level 2 Depth / Length	150 mm
Package Level 2 Height	105 mm
Package Level 2 Gross Weight	0.45 kg
Package Level 2 EAN	4013614550973
Package Level 2 Units	box 10 piece

Classifications	
Object Classification Code	K
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	39121529
E-Number (Finland)	3709743

Categories
Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

