




PRODUCT-DETAILS

MC2A400AT4

MC2A400AT4 Mini Contactor 120 V AC - 4 NO - 0 NC - Screw Terminals



General Information

Extended Product Type	MC2A400AT4
Product ID	1SAL101647R9902
EAN	4013614544316
Catalog Description	MC2A400AT4 Mini Contactor 120 V AC - 4 NO - 0 NC - Screw Terminals
Long Description	The MC2A400AT4 mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is suitable for wall or rail mounting.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Popular Downloads

Instructions and Manuals	2CDC103061M6801
CAD Dimensional	2CDC001079B0201

Drawing

Dimensions

Product Net Width	45 mm
Product Net Height	48 mm
Product Net Depth / Length	56 mm
Product Net Weight	0.17 kg

Technical

Number of Poles	4
Mini Contactor Type	Mini Contactor
Rated Operational Voltage	Main Circuit 690 V AC Main Circuit 440 V DC
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz Main Circuit 50 Hz Main Circuit 60 Hz Main Circuit DC
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 6 kV
Rated Insulation Voltage (U _i)	750 V
Number of Main Contacts NC	0
Number of Main Contacts NO	4
Rated Operational Current AC-1 (I _e)	(690 V) 55 °C 20 A (690 V) 70 °C 16 A (230 V) 55 °C 20 A (230 V) 70 °C 16 A (400 V) 55 °C 20 A (400 V) 70 °C 16 A (500 V) 55 °C 20 A (500 V) 70 °C 16 A
Rated Operational Power AC-3 (P _e)	(230 V) Three Phase 3 kW (400 V) Three Phase 5.5 kW (500 V) Three Phase 5.5 kW (690 V) Three Phase, NO 4 kW
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 96 A
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Conventional Free-air Thermal Current (I _{th})	Main Circuit 20 A
Rated Control Circuit Voltage (U _c)	120 V AC
Coil Operating Limits	(acc. to IEC 60947-4-1) for AC supply 0.85 ... 1.1 x U _c (at θ ≤ 55 °C)
Degree of Protection	Control Circuit Terminals IP20 Main Circuit Terminals IP20
Mechanical Durability	10000000 cycle
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-15) 360 cycles per hour (AC-3) 1200 cycles per hour (DC-1) 600 cycles per hour (DC-13) 360 cycles per hour (DC-3) 600 cycles per hour
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm² Flexible with Ferrule 2x 0.75 ... 1.5 mm² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²

	Flexible 1/2x 0.75 ... 2.5 mm² Rigid 1x 0.75 ... 4 mm² Rigid 2x 0.75 ... 2.5 mm²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm² Flexible with Ferrule 2x 0.75 ... 1.5 mm² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm² Flexible 1/2x 0.75 ... 2.5 mm² Rigid 1/2x 0.75 ... 2.5 mm²
Wire Stripping Length	Control Circuit 9 mm Main Circuit 9 mm
Tightening Torque	Control Circuit 0.8 N·m Main Circuit 0.8 ... 1.0 N·m
Recommended Screw Driver	Pozidriv 2
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Power Loss	at Rated Operating Conditions AC-1 per Pole 0.7 W
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Full Load Amps Motor Use	(115 V AC) Single Phase 9.8 A (200 V AC) Three Phase 11 A (220 ... 240 V AC) Three Phase 9.6 A (230 V AC) Single Phase 12 A (440 ... 480 V AC) Three Phase 11 A (550 ... 600 V AC) Three Phase 11 A
Horsepower Rating UL/CSA	(115 V AC) Single Phase 0.5 Hp (200 V AC) Three Phase 3 Hp (220 ... 240 V AC) Three Phase 3 Hp (230 V AC) Single Phase 2 Hp (440 ... 480 V AC) Three Phase 7.5 Hp (550 ... 600 V AC) Three Phase 10 Hp
General Use Rating UL/CSA	(600 V AC) 20 A
Connecting Capacity Main Circuit UL/CSA	Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Control Circuit 7 in·lb Main Circuit 7 in·lb

Environmental

Ambient Air Temperature	Operation -40 ... +70 °C Storage -55 ... +80 °C
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations	5g 3 ... 150 Hz

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

BV Certificate	1SAA971000-0201
CB Certificate	1SAA971000-2001
CQC Certificate	CQC2019010304197131
Declaration of Conformity - CCC	2020980304001602
Declaration of Conformity - CE	1SAD101100-3201
Declaration of Conformity - UKCA	1SAD201100-3201
RINA Certificate	1SAA971001-0801
UL Certificate	E191658-19880826

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	46 mm
Package Level 1 Height	58 mm
Package Level 1 Depth / Length	49 mm
Package Level 1 Gross Weight	0.175 kg
Package Level 1 EAN	4013614544316
Package Level 2 Units	box 20 piece
Package Level 2 Width	237 mm
Package Level 2 Height	120 mm
Package Level 2 Depth / Length	102 mm
Package Level 2 Gross Weight	3.55 kg
Package Level 2 EAN	4013614544767

Classifications

Object Classification Code	Q
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
E-Number (Finland)	3709496

Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

