



PRODUCT-DETAILS

SHUNT OPEN.REL.ADDIT. 440V AC E1/6-T8

SHUNT OPEN.REL.ADDIT. 440V AC E1/6-T8



General Information	
Extended Product Type	SHUNT OPEN.REL.ADDIT. 440V AC E1/6-T8
Product ID	1SDA050166R1
EAN	8015644502898
Catalog Description	SHUNT OPEN.REL.ADDIT. 440V AC E1/6-T8
Long Description	ADDITIONAL SHUNT OPENING RELEASE SUPPLY VOLTAGE 440V AC E1/6-T8

Circular Value	
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Environmental	
Environmental Information	1SDL000145R0
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644502898
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Weight	1 kg
--------------------	------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Gross Weight	0.9 kg
Package Level 1 EAN	8015644502898

Additional Information

Configuration Type	Loose or configurable
Current Type	AC
Product Main Type	Accessories for Emax
Product Name	Accessory
Product Type	Accessory
Rated Voltage (U _r)	440 V AC
Standards	IEC
Suitable For	E1, E2, E3, E4, E6, T8
Suitable for Product Class	SACE Emax, SACE Tmax T

Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0013
	1SDL000165R0014
	1SDL000165R0015
	1SDL000165R0016
	1SDL000165R0017
	1SDL000165R0008
Instructions and Manuals	1SDC200006D0209

Classifications

ETIM 7	EC002483 - Switch spool for power circuit breaker
ETIM 8	EC002483 - Switch spool for power circuit breaker
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Accessories for Emax

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Accessories for Emax (old)

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax T

