



PRODUCT-DETAILS

T5D 400 4p F F

T5D 400 4p F F



General Information	
Extended Product Type	T5D 400 4p F F
Product ID	1SDA054600R1
EAN	8015644556983
Catalog Description	T5D 400 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX T5D 400 FIXED FOUR-POLE WITH FRONT TERMINALS

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental Information	9AKK10103A1056
	9AKK108467A6707

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	589159d5-0945-415f-8498-665412027854 Italy (IT)
Simplified SCIP	aa73c34b-fd1b-4137-853b-6aab5474bba0 Germany (DE) bcb09c46-4b46-425f-9db8-951888f274a6 Poland (PL) 1a4acb0f-173b-4f15-9df6-63979fe0cb7b Germany (DE) bb1fb6f8-1e39-409b-bc4c-b7aaf94d9b9a Poland (PL) e2f43e0a-04a8-437d-816a-5dc709ec73b0 Norway (NO) 1201cb38-5614-4f57-b49e-1cc7c9873aed France (FR) b07bd7f3-3f88-4107-b8e6-223622229815 Sweden (SE) e8f46076-d043-4b25-887b-9b7b0bf7597b Germany (DE) af39ee33-d129-4d8d-97bd-23a75c6cf39c France (FR) 80ed9396-d3c0-4898-ae06-fb2bd4e6fe11 Netherlands (NL) 55bfe880-90d4-4340-9ab8-d9b6d4c44de0 Spain (ES) 46f71b8d-7b71-4e43-8dbc-d0f22d2bea84 Netherlands (NL) 54ef9ea8-d92f-4348-8ab3-a0c69ee38e78 Finland (FI) 440853a0-f494-4fe3-8fc8-481d8807702c Netherlands (NL) 3fd445d0-de8f-47be-951a-16b6fd797b2a Germany (DE) 94305b50-34f0-4b00-8d9a-52cd83bf5fcf Germany (DE) c17a6f49-3c47-4d48-89a9-06cb72ab0d82 Croatia (HR) 7f76282f-4cc7-42c0-9bdf-48aa3a5aa52a Czech Republic (CZ) ed7aca7e-0ff0-4ddd-aa06-50caa3eee911 Poland (PL) 3189dfc3-cab5-40fd-b865-898df3ff479d Netherlands (NL) 328e1385-c6fb-4339-a37e-d397e571ca75 Netherlands (NL) 4e9f5e44-6edb-451e-8ca4-2fe1c653349b Estonia (EE) 41ce5e52-aa69-4787-9961-c5b7b9b0a260 Portugal (PT) 5667a9d9-ac36-419e-9dbd-08550fb3e584 Sweden (SE) ce7c75e6-1358-465b-b96a-f753940497b3 Denmark (DK) 66a76ad5-468b-48c7-a398-6d831820764d Greece (GR) 848360e4-0160-424d-919d-9d2a64e9b1fd Bulgaria (BG)

Ordering

E-Number (Finland)	3655614
EAN	8015644556983
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	5.472 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.76 kg
Package Level 1 EAN	8015644556983

Additional Information	
Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 16.5 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 6 A
Rated Uninterrupted Current (I _u)	400 A
Short-Circuit Performance Level	D
Standards	IEC
Sub-type	T5
Suitable For	T5
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test})	3000 V
Test Voltage at Industrial Frequency for 1 Minute	3000 V
Version	F

Certificates and Declarations	
Data Sheet, Technical Information	1SDC210004D0203
Declaration of Conformity - CE	9AKK106713A5539
Instructions and Manuals	1SDH000437R0001
Instructions and Manuals (Part 2)	ITSCE-RH0100001

Classifications	
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

