



PRODUCT-DETAILS

T5 400 P FP 3p EF

T5 400 P FP 3p EF

| General Information   |                                                                                       |
|-----------------------|---------------------------------------------------------------------------------------|
| Extended Product Type | T5 400 P FP 3p EF                                                                     |
| Product ID            | 1SDA054749R1                                                                          |
| EAN                   | 8015644558703                                                                         |
| Catalog Description   | T5 400 P FP 3p EF                                                                     |
| Long Description      | FIXED PART PLUG-IN FOR C.BREAKER TMAX THREE-POLE WITH EXTENDED FRONT TERMINALS T5 400 |

| Circular Value                              |                 |
|---------------------------------------------|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326 |

| Environmental |                 |
|---------------|-----------------|
| Environmental | 9AKK108467A6707 |

Information

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| REACH Declaration | 9AKK108466A1425                                                        |
| RoHS Information  | 9AKK108466A1424                                                        |
| RoHS Status       | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Ordering

|                          |               |
|--------------------------|---------------|
| Order Code US and Canada | KT5PFEF       |
| E-Number (Finland)       | 3655563       |
| E-Number (Sweden)        | 3180874       |
| EAN                      | 8015644558703 |
| Minimum Order Quantity   | 1 piece       |
| Customs Tariff Number    | 85389099      |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 171 mm |
| Product Net Height         | 209 mm |
| Product Net Depth / Length | 50 mm  |
| Product Net Weight         | 1.5 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 131 mm        |
| Package Level 1 Height         | 131 mm        |
| Package Level 1 Depth / Length | 313 mm        |
| Package Level 1 Gross Weight   | 1.708 kg      |
| Package Level 1 EAN            | 8015644558703 |

## Additional Information

|                                               |                                            |
|-----------------------------------------------|--------------------------------------------|
| Device                                        | Fixed Part                                 |
| Number of Poles                               | 3                                          |
| Product Main Type                             | Accessories for Tmax T                     |
| Product Name                                  | Accessory                                  |
| Product Type                                  | Fixed Part                                 |
| Rated Operational Voltage                     | 690 V AC<br>750 V DC                       |
| Rated Uninterrupted Current (I <sub>u</sub> ) | 400 A                                      |
| RoHS Date                                     | NA                                         |
| Standards                                     | IEC                                        |
| Sub-type                                      | T5                                         |
| Suitable For                                  | T5                                         |
| Suitable for Product Class                    | Moulded Case Circuit Breakers              |
| Terminal Connection Type                      | Plug-In Circuit-Breakers<br>Front Extended |
| Test Voltage at Industrial                    | not applicable V                           |

Frequency for 1 Minute

|         |   |
|---------|---|
| Version | P |
|---------|---|

Certificates and Declarations

|                                   |                                                             |
|-----------------------------------|-------------------------------------------------------------|
| Data Sheet, Technical Information | 1SDC210004D0203                                             |
| Declaration of Conformity - CE    | Refer to the EU Declaration of the relative Circuit Breaker |
| Instructions and Manuals          | 1SDH000437R0001                                             |
| Instructions and Manuals (Part 2) | ITSCE-RH0100001                                             |

Classifications

|                                    |                                                            |
|------------------------------------|------------------------------------------------------------|
| ETIM 7                             | EC002043 - Chassis part power circuit breaker              |
| ETIM 8                             | EC002043 - Chassis part power circuit breaker              |
| ETIM 9                             | EC002043 - Chassis part power circuit breaker              |
| IDEA Granular Category Code (IGCC) | 5219 >> Switch part or accessory                           |
| Object Classification Code         | Q                                                          |
| UNSPSC                             | 39122221                                                   |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass                             | V11.1 : 27370422                                           |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T