



PRODUCT-DETAILS

E3H1250PR121/P-LIIn=1250A4pFHR
E3H 1250 PR121/P-LI In=1250A 4p F HR



General Information	
Extended Product Type	E3H1250PR121/P-LIIn=1250A4pFHR
Product ID	1SDA056376R1
EAN	8015644577162
Catalog Description	E3H 1250 PR121/P-LI In=1250A 4p F HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3H 1250A FOUR-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR121/P-LI R1250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Circular Value	
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Environmental	
Environmental Information	9AKK10103A6076
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644577162
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	530 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	76 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 Gross Weight	90 kg
Package Level 1 EAN	8015644577162

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 12000 cycle Ue = 500 ... 690 V 12000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	4
Power Loss	60 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1250 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current (I _e)	1250 A
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 85 kA (660 V AC) 85 kA (690 V AC) 85 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 75 kA for 3 s 65 kA

Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 100 kA
	(230 V AC) 100 kA
	(380 V AC) 100 kA
	(400 V AC) 100 kA
	(415 V AC) 100 kA
	(440 V AC) 100 kA
	(500 V AC) 100 kA
	(660 V AC) 85 kA
	(690 V AC) 85 kA
Rated Uninterrupted Current (I _u)	1250 A
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200006D0209
Declaration of Conformity - CE	1SDL000165R0015
Instructions and Manuals	1SDH000460R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

