



PRODUCT-DETAILS

E2S2000PR122/P-LSIRcIn=2000A4pFHR

E2S 2000 PR122/P-LSIRc In=2000A 4p F HR



| General Information   |                                                                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E2S2000PR122/P-LSIRcIn=2000A4pFHR                                                                                                                                                                 |
| Product ID            | 1SDA058683R1                                                                                                                                                                                      |
| EAN                   | 8015644610296                                                                                                                                                                                     |
| Catalog Description   | E2S 2000 PR122/P-LSIRc In=2000A 4p F HR                                                                                                                                                           |
| Long Description      | SACE EMAX CIRCUIT-BREAKER E2S 2000A FOUR-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/P-LSIRc R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

| Circular Value                              |                                 |
|---------------------------------------------|---------------------------------|
| Conflict Minerals Reporting Template (CMRT) | Document availability on demand |

| Environmental             |                |
|---------------------------|----------------|
| Environmental Information | 9AKK10103A6076 |

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| REACH Declaration | 9AKK108466A1425                                                        |
| RoHS Information  | 9AKK108466A1424                                                        |
| RoHS Status       | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644610296 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 386 mm |
| Product Net Height         | 418 mm |
| Product Net Depth / Length | 302 mm |
| Product Net Weight         | 56 kg  |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 515 mm        |
| Package Level 1 Height         | 600 mm        |
| Package Level 1 Depth / Length | 615 mm        |
| Package Level 1 Gross Weight   | 68 kg         |
| Package Level 1 EAN            | 8015644609139 |

Additional Information

|                                                     |                                                                                |
|-----------------------------------------------------|--------------------------------------------------------------------------------|
| Current Type                                        | AC                                                                             |
| Electrical Durability                               | Ue =< 440 V 10000 cycle<br>Ue = 500 ... 690 V 8000 cycle<br>30 cycles per hour |
| Mechanical Durability                               | 25000 cycle<br>60 cycles per hour                                              |
| Number of Poles                                     | 4                                                                              |
| Power Loss                                          | 180 W                                                                          |
| Product Main Type                                   | SACE Emax                                                                      |
| Product Name                                        | Air Circuit Breaker                                                            |
| Product Type                                        | Air Circuit Breaker                                                            |
| Rated Current (I <sub>n</sub> )                     | 2000 A                                                                         |
| Rated Voltage (U <sub>r</sub> )                     | 690 V                                                                          |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 12 kV                                                                          |
| Rated Insulation Voltage (U <sub>i</sub> )          | 1000 V                                                                         |
| Rated Operational Current (I <sub>a</sub> )         | 2000 A                                                                         |
| Rated Operational Voltage                           | 690 V AC                                                                       |
| Rated Service Short-Circuit Breaking                | (220 V AC) 85 kA<br>(230 V AC) 85 kA                                           |

|                                                                          |                                                                                                                                                                                  |
|--------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacity (I <sub>cs</sub> )                                              | (380 V AC) 85 kA<br>(400 V AC) 85 kA<br>(415 V AC) 85 kA<br>(440 V AC) 85 kA<br>(500 V AC) 65 kA<br>(660 V AC) 65 kA<br>(690 V AC) 65 kA                                         |
| Rated Short-time<br>Withstand Current Low<br>Voltage (I <sub>cw</sub> )  | for 1 s 65 kA<br>for 3 s 50 kA                                                                                                                                                   |
| Rated Ultimate Short-<br>Circuit Breaking<br>Capacity (I <sub>cu</sub> ) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(380 V AC) 85 kA<br>(400 V AC) 85 kA<br>(415 V AC) 85 kA<br>(440 V AC) 85 kA<br>(500 V AC) 65 kA<br>(660 V AC) 65 kA<br>(690 V AC) 65 kA |
| Rated Uninterrupted<br>Current (I <sub>u</sub> )                         | 2000 A                                                                                                                                                                           |
| Release                                                                  | PR122/P-LSIRc                                                                                                                                                                    |
| Release Type                                                             | EL                                                                                                                                                                               |
| Short-Circuit<br>Performance Level                                       | S                                                                                                                                                                                |
| Standards                                                                | IEC                                                                                                                                                                              |
| Sub-type                                                                 | E2                                                                                                                                                                               |
| Terminal Connection<br>Type                                              | Fixed Circuit-Breakers<br>Rear flat Horizontal                                                                                                                                   |
| Version                                                                  | F                                                                                                                                                                                |

Certificates and Declarations

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Data Sheet, Technical<br>Information | 1SDC200006D0209                    |
| Declaration of<br>Conformity - CE    | 1SDL000165R0014                    |
| Instructions and<br>Manuals          | 1SDH000460R0002<br>1SDH000460R0102 |

Classifications

|                               |                                                                              |
|-------------------------------|------------------------------------------------------------------------------|
| ETIM 7                        | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                        | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification<br>Code | Q                                                                            |
| WEEE Category                 | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

