



PRODUCT-DETAILS

T5H-D 400 MCS-UL/CSA Im=5000 4p F F

T5H-D 400 MCS-UL/CSA Im=5000 4p F F



General Information	
Extended Product Type	T5H-D 400 MCS-UL/CSA Im=5000 4p F F
Product ID	1SDA060124R1
EAN	8015644625702
Catalog Description	T5H-D 400 MCS-UL/CSA Im=5000 4p F F
Long Description	SWITCH-DISCONNECTOR TMAX T5H-D 400 MCS-UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS Im 5000 A
Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
Environmental	
Environmental	9AKK10103A1056

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	T5H400DW-4
EAN	8015644625702
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.15 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	4.5 kg
Package Level 1 EAN	8015644625702

Additional Information

Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 19.5 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter
Rated Operational Voltage	600 V AC 600 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 6 kA
Rated Uninterrupted Current (I_u)	400 A
Short-Circuit Performance Level	H
Standards	UL CSA C22.3
Sub-type	T5
Suitable For	T5
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

Certificates and Declarations

Data Sheet, Technical Information	9AKK105713A5947
Declaration of Conformity - CE	9AKK106713A5539
GL Certificate	1SDL000163R0062
Instructions and Manuals	1SDC210023D0201

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

