




PRODUCT-DETAILS

T7-X1 W FP 3p EF-EF
T7-X1 W FP 3p EF-EF



General Information

Extended Product Type	T7-X1 W FP 3p EF-EF
Product ID	1SDA062045R1
EAN	8015644645830
Catalog Description	T7-X1 W FP 3p EF-EF
Long Description	FIXED PART WITHDRAWABLE FOR C.BREAKER TMAX-EMAX THREE-POLE WITH EXTENDED FRONT TERMINALS T7-X1

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

EAN	8015644645830
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Product Net Width	278 mm
Product Net Height	343 mm
Product Net Depth / Length	251 mm
Product Net Weight	18 kg

Package Level 1 Units	1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	340 mm
Package Level 1 Depth / Length	380 mm
Package Level 1 Gross Weight	19.5 kg
Package Level 1 EAN	8015644645830

Number of Poles	3
Product Main Type	Accessories for Tmax T
Product Name	Accessory
Product Type	Fixed Part
Rated Operational Voltage	690 V AC
Rated Uninterrupted Current (I _u)	1600 A
Standards	IEC
Sub-type	T7-X1
Terminal Connection Type	Withdrawable Circuit-Breakers Front Extended
Version	W

Data Sheet, Technical Information	1SDC210015D0208 1SDC210300D0201
Declaration of Conformity - CE	Refer to the EU Declaration of the relative Circuit Breaker
Instructions and Manuals	1SDH000529R0802 1SDH000529R0807

ETIM 7	EC002043 - Chassis part power circuit breaker
ETIM 8	EC002043 - Chassis part power circuit breaker
ETIM 9	EC002043 - Chassis part power circuit breaker
Object Classification Code	Q

UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370422

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax
Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

