



PRODUCT-DETAILS

KIT EF FP T7-T7M-X1 3pcs

KIT EF FP T7-T7M-X1 3pcs



General Information	
Extended Product Type	KIT EF FP T7-T7M-X1 3pcs
Product ID	1SDA062171R1
EAN	8015644647100
Catalog Description	KIT EF FP T7-T7M-X1 3pcs
Long Description	FRONT TERMINALS 3pcs FOR FIXED PART T7-T7M-X1

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental Information	9AKK108467A6707

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	KT7XWEF-3
EAN	8015644647100
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Weight	1 kg
--------------------	------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	165 mm
Package Level 1 Height	65 mm
Package Level 1 Depth / Length	270 mm
Package Level 1 Gross Weight	0.5 kg
Package Level 1 EAN	8015644647100

Additional Information

Configuration Type	Loose or configurable
Number of Poles	3
Product Main Type	Accessories for Tmax T
Product Name	Accessory
Product Type	Accessory
Standards	IEC
Suitable For	T7, X1
Suitable for Product Class	SACE Emax SACE Tmax T

Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0208 1SDC210300D0201
Declaration of Conformity - CE	Refer to the EU Declaration of the relative Circuit Breaker
Instructions and Manuals	1SDH000529R0807

Classifications

ETIM 7	EC002019 - Connection vane/phase spreader
ETIM 8	EC002019 - Connection vane/phase spreader

ETIM 9	EC002019 - Connection vane/phase spreader
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371305

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Accessories for Emax
Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax T

