



PRODUCT-DETAILS**T7S 1250 PR232/P LSI In=1250A 3p F F****T7S 1250 PR232/P LSI In=1250A 3p F F**

General Information

Extended Product Type	T7S 1250 PR232/P LSI In=1250A 3p F F
Product ID	1SDA062867R1
EAN	8015644654160
Catalog Description	T7S 1250 PR232/P LSI In=1250A 3p F F
Long Description	C.BREAKER TMAX T7S 1250 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC PR232/P-LSI R 1250

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental	9AKK10103A1059
---------------	----------------

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	da03da0a-bc7d-4078-8477-a5a073e63e1f Italy (IT)
Simplified SCIP	c8ce81f6-bfcb-42ba-a05c-6b71a3c567c0 Germany (DE) b765c4b8-b7eb-4ffb-884b-d1acfc9764b8 Norway (NO) 66256520-6d6c-4cfe-b684-a1b0856260ea Germany (DE) 8fd7d2f5-ec4c-48d7-91e2-34c13d29f1ce Croatia (HR) 8be606ef-b7c8-48c2-8c7c-1a400706692b Netherlands (NL) 4c600c92-1c40-43f5-bcf7-84f411d16f8c Estonia (EE) 4b62ee63-d814-465c-a306-78b957520a1f Portugal (PT) afdc82c4-0956-49ae-8ccc-b160a90bc7d1 Netherlands (NL) 65d192c9-2e5e-4381-bc95-570682c45d8f Finland (FI) 8378ab53-e951-490c-970f-d311b336b62e Sweden (SE) 81950776-3d4b-4d63-a9ed-fe3a75cd01ea Poland (PL) 80171f53-f048-4e80-8014-1ce3c97a9128 Germany (DE) 499cbd00-ae72-4794-99c5-1c9c249f8f57 France (FR) 16d474e1-a616-4664-bc87-cd14348f08a7 Netherlands (NL) 0a266a94-cce8-4a73-8b9a-b0143069213e Spain (ES) 5f2860f8-fd7a-4aea-8f8c-bd0e84755184 Netherlands (NL) a4754275-a403-4c0b-b594-8235d791d58d Denmark (DK) cee814fc-6744-4eaf-8b01-bde87c9ee716 Poland (PL) e65b699a-e848-4578-b21d-d1c574efffb9 Poland (PL) 330760d2-6a8f-4cec-8e31-d050933fb231 France (FR) e55ab0ae-08f0-439c-a194-a0ed98e305d5 Netherlands (NL) ab77f919-4c29-4bdf-84a5-3a45fb9ccfbb Czech Republic (CZ) 2d00309a-6e69-4d4a-bc70-f043a40184e4 Sweden (SE) db5548aa-45de-467e-8e02-a24aa0840f83 Bulgaria (BG) 2c587e85-34c2-46af-8052-884be70d488b Germany (DE) 93aac55c-08d2-4989-aef4-b9bf492fb487 Greece (GR) 1e9efd3c-5e5e-498a-8c1d-3f03ecb997ed Germany (DE)

Ordering

EAN	8015644654160
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	268 mm
Product Net Depth / Length	154 mm
Product Net Weight	14.371 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	280 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	14.372 kg
Package Level 1 EAN	8015644654160

Additional Information

Electrical Durability	2000 cycle 60 cycles per hour
Mechanical Durability	10000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 47 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	1250 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
Rated Uninterrupted Current (I_u)	1250 A
Release	PR232/P-LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	T7
Suitable For	T7
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0201
Declaration of Conformity - CE	9AKK106713A5537
GL Certificate	1SDL000163R0055
Instructions and	1SDC210015D0201

Manuals

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T