




---

 PRODUCT-DETAILS

# T7H 1250 PR232/P LSI In=1250A 4p F F

# T7H 1250 PR232/P LSI In=1250A 4p F F




---

**General Information**

Extended Product Type	T7H 1250 PR232/P LSI In=1250A 4p F F
Product ID	1SDA062907R1
EAN	8015644654566
Catalog Description	T7H 1250 PR232/P LSI In=1250A 4p F F
Long Description	C.BREAKER TMAX T7H 1250 FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC PR232/P-LSI R 1250

---

**Circular Value**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

**Environmental**

Environmental Information	9AKK10103A1059 9AKK108467A6707
---------------------------	-----------------------------------

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### Ordering

EAN	8015644654566
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

### Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	154 mm
Product Net Weight	12.5 kg

### Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	8015644654566

### Additional Information

Electrical Durability	2000 cycle 60 cycles per hour
Mechanical Durability	10000 cycle 60 cycles per hour
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 47 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current ( $I_n$ )	1250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA (400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (690 V AC) 31.5 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 20 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 70 kA

	(400 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (690 V AC) 42 kA
Rated Uninterrupted Current (I <sub>u</sub> )	1250 A
Release	PR232/P-LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	T7
Suitable For	T7
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

## Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0201
Declaration of Conformity - CE	9AKK106713A5537
GL Certificate	1SDL000163R0053
Instructions and Manuals	1SDC210015D0201

## Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

