



 PRODUCT-DETAILS

T4V 250 TMD 32-320 3p F FC 1150V AC

T4V 250 TMD 32-320 3p F FC 1150V AC



General Information

Extended Product Type	T4V 250 TMD 32-320 3p F FC 1150V AC
Product ID	1SDA063410R1
EAN	8015644660192
Catalog Description	T4V 250 TMD 32-320 3p F FC 1150V AC
Long Description	C.BREAKER TMAX T4V 250 1150V AC FIXED THREE-POLE WITH FRONT TERMINALS FOR CABLE Cu AND THERMOMAGNETIC RELEASE TMD R 32-320 A

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental	9AKK10103A1057
---------------	----------------

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644660192
Minimum Order Quantity	1 piece
Customs Tariff Number	85352100

Dimensions

Product Net Width	105 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	2.35 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	2.5 kg
Package Level 1 EAN	8015644660192

Additional Information

Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 3.7 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	32 A
Rated Operational Voltage	1150 V AC 1000 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(1000 V AC) 12 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(415 V AC) 200 kA (1000 V AC) 20 kA
Rated Uninterrupted Current (I_u)	250 A
Release	TMD
Release Type	TM
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	T4

Terminal Connection Type	Fixed Circuit-Breakers Front for Copper Cables
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210300D0201
Declaration of Conformity - CE	9AKK106713A5540
GL Certificate	1SDL000163R0061
Instructions and Manuals	1SDH000457R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

