



PRODUCT-DETAILS

T4V250 PR222DS/P-LSIG In250
4pFFC1150VAC

T4V250 PR222DS/P-LSIG In250 4pFFC1150VAC



General Information	
Extended Product Type	T4V250 PR222DS/P-LSIG In250 4pFFC1150VAC
Product ID	1SDA063433R1
EAN	8015644660574
Catalog Description	T4V250 PR222DS/P-LSIG In250 4pFFC1150VAC
Long Description	C.BREAKER TMAX T4V 250 1150V AC FIXED FOUR-POLE WITH FRONT TERMINALS FOR CABLE Cu AND SOLID-STATE RELEASE IN AC PR222DS/P-LSIG R 250

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental	9AKK10103A1057

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644660574
Minimum Order Quantity	1 piece
Customs Tariff Number	85352100

Dimensions

Product Net Width	105 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	3.05 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	3.5 kg
Package Level 1 EAN	8015644660574

Additional Information

Electrical Durability	8000 cycle 120 cycles per hour
Mechanical Durability	20000 cycle 240 cycles per hour
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 10.7 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	250 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1150 V
Rated Operational Voltage	1150 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(1000 V AC) 12 kA (1150 V AC) 6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(1000 V AC) 20 kA (1150 V AC) 12 kA

Rated Uninterrupted Current (I _u)	250 A
Release	PR222DS/P-LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	T4
Terminal Connection Type	Fixed Circuit-Breakers Front for Copper Cables
Test Voltage Max (U _{test})	3500 V
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210300D0201
Declaration of Conformity - CE	9AKK106713A5540
GL Certificate	1SDL000163R0061
Instructions and Manuals	1SDH000457R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

