



PRODUCT-DETAILS

T5L 400 W FP 3p FC Cu 1000V AC
T5L 400 W FP 3p FC Cu 1000V AC

General Information	
Extended Product Type	T5L 400 W FP 3p FC Cu 1000V AC
Product ID	1SDA063464R1
EAN	8015644660888
Catalog Description	T5L 400 W FP 3p FC Cu 1000V AC
Long Description	FIXED PART WITHDRAWABLE FOR C.BREAKER TMAX T5L 400 1000V AC THREE-POLE WITH FRONT TERMINALS FOR CABLE Cu

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental	9AKK108467A6707

Information

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644660888
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Weight	2.9 kg
--------------------	--------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	158 mm
Package Level 1 Height	158 mm
Package Level 1 Depth / Length	188 mm
Package Level 1 Gross Weight	3.2 kg

Additional Information

Number of Poles	3
Product Main Type	Accessories for Tmax T
Product Name	Accessory
Product Type	Fixed Part
Rated Operational Voltage	1000 V AC
Rated Uninterrupted Current (I _u)	400 A
Short-Circuit Performance Level	L
Standards	IEC
Sub-type	T5
Terminal Connection Type	Withdrawable Circuit-Breakers Front for Copper Cables
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0208 1SDC210300D0201
Declaration of Conformity - CE	Refer to the EU Declaration of the relative Circuit Breaker
Instructions and Manuals	1SDH000569R0001

Classifications		
ETIM 7	EC002043 - Chassis part power circuit breaker	
ETIM 8	EC002043 - Chassis part power circuit breaker	
ETIM 9	EC002043 - Chassis part power circuit breaker	
Object Classification Code		Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
eClass		V11.1 : 27370422

Categories
Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T