




---

 PRODUCT-DETAILS

# T5N400 UL/CSA TMA 400-2000..4000 2p F F

# T5N400 UL/CSA TMA 400-2000..4000 2p F F

---

**General Information**

Extended Product Type	T5N400 UL/CSA TMA 400-2000..4000 2p F F
Product ID	1SDA064133R1
EAN	8015644669942
Catalog Description	T5N400 UL/CSA TMA 400-2000..4000 2p F F
Long Description	C.BREAKER TMAX T5N 400 UL/CSA FIXED TWO-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 400 I3=2000...4000 A

---

**Circular Value**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

---

**Environmental**

Environmental Information	9AKK10103A1056 9AKK108467A6707
REACH Declaration	9AKK108466A1425

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

## Ordering

Order Code US and Canada	T5N400TW-2
EAN	8015644669942
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

---

## Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	3.25 kg

---

## Container Information

Package Level 1 EAN	8015644669942
---------------------	---------------

---

## Additional Information

Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	2
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current ( $I_n$ )	400 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	600 V AC 600 V DC
Rated Uninterrupted Current ( $I_u$ )	400 A
Release	TMA
Release Type	TM
Short-Circuit Performance Level	N
Standards	UL
Sub-type	T5
Suitable For	T5
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

---

## Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 65 kA (480 V AC) 25 kA (600 V AC) 18 kA
-----------------------------------	--

(500 V DC) 2 Poles in Series 25 kA  
(600 V DC) 3 Poles in Series 16 kA

---

## Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5539
Instructions and Manuals	1SDC210023D0201

---

## Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T