



 PRODUCT-DETAILS

T8L 2000 PR331/P L SIG In=2000A 3p F F

T8L 2000 PR331/P L SIG In=2000A 3p F F



General Information

| | |
|-----------------------|---|
| Extended Product Type | T8L 2000 PR331/P L SIG In=2000A 3p F F |
| Product ID | 1SDA065724R1 |
| EAN | 8015644686314 |
| Catalog Description | T8L 2000 PR331/P L SIG In=2000A 3p F F |
| Long Description | C.BREAKER TMAX T8L 2000 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR331/P-LSIG R 2000 |

Circular Value

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

Environmental

| | |
|---------------|-----------------|
| Environmental | 9AKK107046A3003 |
|---------------|-----------------|

| | |
|-------------------|--|
| Information | 9AKK108467A6707 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

| | |
|--------------------------|------------------|
| Order Code US and Canada | T8LFD3GE000000XX |
| EAN | 8015644686314 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width | 427 mm |
| Product Net Height | 382 mm |
| Product Net Depth / Length | 282 mm |
| Product Net Weight | 68 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 525 mm |
| Package Level 1 Height | 475 mm |
| Package Level 1 Depth / Length | 695 mm |
| Package Level 1 Gross Weight | 78 kg |
| Package Level 1 EAN | 8015644686314 |

Additional Information

| | |
|--|--|
| Electrical Durability | 4500 cycle 20 cycles per hour |
| Mechanical Durability | 15000 cycle 60 cycles per hour |
| Number of Poles | 3 |
| Power Loss | at Rated Operating Conditions per Pole 46 W |
| Product Main Type | SACE Tmax T |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | Automatic Circuit Breaker |
| Rated Current (I_n) | 2000 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA |

| | |
|---|--|
| | (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 40 A |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA |
| Rated Uninterrupted Current (I_u) | 2000 A |
| Release | PR331/P LSIg |
| Release Type | EL |
| Short-Circuit Performance Level | L |
| Standards | IEC |
| Sub-type | T8 |
| Terminal Connection Type | Fixed Circuit-Breakers Front |
| Version | F |

Certificates and Declarations

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210023D0201 |
| Declaration of Conformity - CE | 9AKK106713A5533 |
| Wiring Diagram | 1SDM000061R0001 |
| Instructions and Manuals | 1SDC210033D0202 |

Classifications

| | |
|------------------------------------|--|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers |
| Object Classification Code | Q |
| UNSPSC | 39121616 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370409 |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

