



PRODUCT-DETAILS

T8V 2000 UL PR332/P L SIG In=2000A 3p F F

T8V 2000 UL PR332/P L SIG In=2000A 3p F F



General Information	
Extended Product Type	T8V 2000 UL PR332/P L SIG In=2000A 3p F F
Product ID	1SDA065880R1
EAN	8015644687922
Catalog Description	T8V 2000 UL PR332/P L SIG In=2000A 3p F F
Long Description	C.BREAKER TMAX T8V 2000 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR332/P-L SIG R 2000"

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental	9AKK107046A3003

Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	T8VBD3GS000000XX
EAN	8015644687922
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	427 mm
Product Net Height	382 mm
Product Net Depth / Length	282 mm
Product Net Weight	9.7 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	525 mm
Package Level 1 Height	475 mm
Package Level 1 Depth / Length	695 mm
Package Level 1 Gross Weight	11.2 kg
Package Level 1 EAN	8015644687922

Additional Information

Electrical Durability	4500 cycle 20 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 46 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I_n)	2000 A
Rated Operational Voltage	600 V AC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR332/P LSIG
Release Type	EL
Short-Circuit Performance Level	V

Standards	UL
Sub-type	T8
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U _{test})	3500 V
Version	F

Certificates and Declarations

Data Sheet, Technical Information	9AKK107991A5458 9AKK105713A5947
Declaration of Conformity - CE	1SDL000165R0008 9AKK106713A5533
Wiring Diagram	
Instructions and Manuals	1SDC210023D0201

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

