



PRODUCT-DETAILS

T7D/PV 1250 4p F F 1100V DC

T7D/PV 1250 4p F F 1100V DC



General Information

Extended Product Type	T7D/PV 1250 4p F F 1100V DC
Product ID	1SDA069826R1
EAN	8015644705954
Catalog Description	T7D/PV 1250 4p F F 1100V DC
Long Description	SWITCH-DISCONNECTOR TMAX T7D/PV 1250 1100V DC FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK10103A1059 9AKK108467A6707
REACH Declaration	9AKK108466A1425

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	9b9707e3-f6bf-4431-84a5-c14187f48597 Italy (IT)
Simplified SCIP	c1206535-1039-4e2f-87d0-31d4eb0328ce Germany (DE) 565d093d-43d2-4a86-8db1-e254fde0ca0f Norway (NO) c3f0934d-3fd4-4b25-98ec-60e5cceb96f9 Poland (PL) c10c2fda-5e85-4c45-b8ec-e61b38a7fd93 Netherlands (NL) 6faca3b8-b9bb-45fc-86c5-8b47d8a6285d Netherlands (NL) 61bc0fbf-24b8-4b23-b9f7-f6ab316c323a Estonia (EE) 6fc0c7de-d481-419c-b27e-dcf48d53d449 Greece (GR) 128d4a1c-bf8e-4d18-8b82-565f6090ae55 Portugal (PT) 7a88a6a9-0992-4e1a-9334-26f37f3d863f Sweden (SE) c839467f-e24f-46a4-928c-ae90d0d52007 Poland (PL) ff0e45b1-d948-4e94-a47f-11af04c62ddb France (FR) bda4aba1-8708-4754-94a4-09917cb59149 Bulgaria (BG) f89763e7-beee-4943-b450-3bc2958b471f Sweden (SE) 7184a569-94b6-491b-a145-0d4357bf63b3 Germany (DE) 5e038119-bfb9-42e4-89ce-f4f42c424966 Germany (DE) a0b8a7ae-60d3-4d4a-a5e5-6974e578a18d Finland (FI) 5265a058-74d6-4afe-acf6-9bd4b8392f10 Netherlands (NL) b6acf9bb-335d-46d6-9186-664beb2fb105 Germany (DE) 11fcc79a-5f0b-4d14-b6e9-020c42e681e0 Denmark (DK) 94b313ea-6b13-47d7-8e79-2cad4fa1a8d5 Germany (DE) a63e8c31-f779-4cbb-92a8-18fee0c53f9c Croatia (HR) 5b693c37-7dfe-4084-a390-76b8735230f5 Czech Republic (CZ) 50991556-b6a3-466a-bc72-5a296f83bdd France (FR) 4e26d3be-8741-4774-a68d-01b9a1d0e2ed Netherlands (NL) 553b91b9-156f-4889-add2-cd36c758c399 Spain (ES) 2c3ec33c-72e4-4e95-a699-39447b10574a Netherlands (NL) bb2186ad-e431-43dd-8fd6-446dad735766 Poland (PL)

Ordering

EAN	8015644705954
Minimum Order Quantity	1 piece
Customs Tariff Number	85352100

Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	154 mm
Product Net Weight	12.5 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	14 kg
Package Level 1 EAN	8015644705954

Additional Information

Current Type	DC
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 47 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	Switch Disconnecter

Rated Current (I_n)	1250 A
Rated Voltage (U_r)	1100 V DC
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1100 V DC
Rated Operational Voltage	1100 V DC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 19.2 kA
Rated Uninterrupted Current (I_U)	1250 A
Short-Circuit Performance Level	D
Standards	IEC
Sub-type	T7
Suitable For	T7
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210300D0201
Declaration of Conformity - CE	9AKK106713A9778
Instructions and Manuals	1SDH000789R0002

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

