



PRODUCT-DETAILS

E1.2N 250 Ekip Hi-Touch LSIG 3p F F

E1.2N 250 Ekip Hi-Touch LSIG 3p F F



General Information	
Extended Product Type	E1.2N 250 Ekip Hi-Touch LSIG 3p F F
Product ID	1SDA070699R1
EAN	8015644745493
Catalog Description	E1.2N 250 Ekip Hi-Touch LSIG 3p F F
Long Description	C.BREAKER EMAX2 E1.2N 250 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSIG R 250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2360
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1900 9AKK108468A3028
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	Z1NMECBK200A000000XX
EAN	8015644745493
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	210 mm
Product Net Height	296 mm
Product Net Depth / Length	183 mm
Product Net Weight	14 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	16 kg
Package Level 1 EAN	8015644745493

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	31 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker

Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I _{cs})	100 %
Rated Current (I _n)	250 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 50 kA for 3 s 30 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I _u)	250 A
Release	Ekip Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E1.2
Terminal Connection Type	Front
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
Instructions and Manuals	1SDH000999R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

