



PRODUCT-DETAILS

E2.2S 800 Ekip G Hi-Touch LSIG 3p F HR

E2.2S 800 Ekip G Hi-Touch LSIG 3p F HR



General Information	
Extended Product Type	E2.2S 800 Ekip G Hi-Touch LSIG 3p F HR
Product ID	1SDA070910R1
EAN	8015644747602
Catalog Description	E2.2S 800 Ekip G Hi-Touch LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2S 800 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/G/HI-TOUCH-LSIG R 800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template
(CMRT)

End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1902
	9AKK108468A1909

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	Z2SPEFBQ200A000000XX
EAN	8015644747602
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	41 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	46 kg
Package Level 1 EAN	8015644747602

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle

	30 cycles per hour
Mechanical Durability	25000 cycle
	60 cycles per hour
Number of Poles	3
Power Loss	34 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs})	100 %
Rated Current (I _n)	800 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I _u)	800 A
Release	Ekip G Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications		
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection	
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection	
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection	
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers	
Object Classification Code	Q	
UNSPSC	39121615	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
eClass	V11.1 : 27370409	

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

