



PRODUCT-DETAILS

E4.2V 2500 Ekip Dip LSIG 3p F HR

E4.2V 2500 Ekip Dip LSIG 3p F HR



General Information	
Extended Product Type	E4.2V 2500 Ekip Dip LSIG 3p F HR
Product ID	1SDA071123R1
EAN	8015644749736
Catalog Description	E4.2V 2500 Ekip Dip LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E4.2V 2500 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2363
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1904
	9AKK108468A1910

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	d6a77472-7870-41be-a2fb-45c650173dd0 Italy (IT)
Simplified SCIP	3e69484b-e30e-4b50-9fd7-2ad6eb8b9b04 Germany (DE) fac2ac51-f936-4676-af1a-09f9c8b8346c Greece (GR) 59ab615a-030d-49a9-aa7e-cf60d28a73ec Estonia (EE) fcbba79e-8fcb-4fc2-87dc-cf9102e6592a Sweden (SE) 4b6c006d-0362-4b60-87e4-60fc384ffe63 Germany (DE) 93e0e603-e475-42f7-8d68-a9f9d857214b Belgium (BE) 501f1b42-769b-45e5-95c5-e5fb5bd86aa5 Bulgaria (BG) ddd90e81-dca0-4c49-92f8-de33b8fc6a8d Germany (DE) cfc6137a-fdcf-4f19-bbe8-fa828af56906 Denmark (DK) a6932c61-fcce-4d33-b01b-132078167178 France (FR) 6a21a9ba-fbb8-4c0e-8e05-8d00642d8020 Croatia (HR) 60fc5c02-da68-40e5-b1e5-f0eef24e4304 Germany (DE) 0f47dead-b275-4f6b-af3d-f1941fdfb832 Germany (DE) 91fd3b31-4f85-4f71-86e1-45608623139b Finland (FI) 0cafed6f-fe21-46b7-9c4a-2acc03093c33 France (FR) fd51c1e1-b0cf-445d-9dfd-544f35ae1bac Netherlands (NL) 2ce23f30-84a9-498b-89b3-efe7457ff1e2 Poland (PL) 2a91ded6-ad0b-4126-a1fa-a954d7bb91a0 Norway (NO) da2641cf-cdc7-4b76-ba3e-c11f7f6c8fcc Hungary (HU) 7bb5413e-d204-435e-a520-66ad71d921eb Poland (PL) Od45ebd1-d8c0-4cc5-88b9-81d8a83f7ee3 Czech Republic (CZ) 759c0129-96b2-4eca-9f19-dd4574dbc8d6 Sweden (SE) 592dbdc3-ecda-4104-a71b-d7d826f0d573 Portugal (PT) fd425ca7-18d9-44c0-a8f0-e9ea6b866217 Poland (PL) 795156c5-6121-4538-88a2-b21ca55dad76 Belgium (BE) a0b1b850-9164-4e5f-9a5a-9c82bd0c2ff5 Spain (ES) b60371d7-e353-4760-b757-1db186562983 Hungary (HU)

Ordering

Order Code US and Canada	Z4VUELBC000A000000XX
EAN	8015644749736
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	384 mm
-------------------	--------

Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	56 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	63 kg
Package Level 1 EAN	8015644749736

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 20 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	425 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I _{cs}	100 %
Rated Current (I _n)	2500 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 100 kA for 3 s 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted	2500 A

Current (I _u)	
Recommended Screw Driver	Main Circuit M12
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E4.2
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m
Version	F
CAD Dimensional Drawing	1SDH001252R0171

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5545
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001001R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

