




---

 PRODUCT-DETAILS

## E6.2V 5000 Ekip Dip LSIG 3p F HR

## E6.2V 5000 Ekip Dip LSIG 3p F HR




---

**General Information**

Extended Product Type	E6.2V 5000 Ekip Dip LSIG 3p F HR
Product ID	1SDA071273R1
EAN	8015644751234
Catalog Description	E6.2V 5000 Ekip Dip LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E6.2V 5000 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

---

**ABB EcoSolutions**

ABB EcoSolutions	Yes
------------------	-----

---

**Circular Value**

Circular Design	Design for Closing Resource Loops - Standard EN45555 - 77 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

**Reporting Template  
(CMRT)**

End of Life Instructions	9AKK108468A2364
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

**Eco Transparency**

Environmental Product Declaration - EPD	9AKK108468A1905
	9AKK108468A1913

**Environmental**

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

**Ordering**

Order Code US and Canada	Z6VXESBC000A000000XX
EAN	8015644751234
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

**Dimensions**

Product Net Width	762 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	109 kg

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	118 kg
Package Level 1 EAN	8015644751234

**Additional Information**

Current Type	AC
Electrical Durability	Ue = < 440 V 3000 cycle Ue = 500 ... 690 V 2000 cycle

	10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	483 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cs</sub>	100 %
Rated Current (I <sub>n</sub> )	5000 A
Rated Voltage (U <sub>r</sub> )	690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U <sub>i</sub> )	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 130 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 100 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 130 kA (525 V AC) 130 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I <sub>u</sub> )	5000 A
Recommended Screw Driver	Main Circuit M12
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E6.2
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m
Version	F
CAD Dimensional Drawing	1SDH001252R0223

## Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed

CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001060R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002

### Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

### Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

