



PRODUCT-DETAILS

E4.2V 4000 Ekip Touch LSiG 4p F HR

E4.2V 4000 Ekip Touch LSiG 4p F HR



General Information	
Extended Product Type	E4.2V 4000 Ekip Touch LSiG 4p F HR
Product ID	1SDA071856R1
EAN	8015644757069
Catalog Description	E4.2V 4000 Ekip Touch LSiG 4p F HR
Long Description	C.BREAKER SACE EMAX2 E4.2V 4000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSiG R 4000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.3 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2363
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1904
	9AKK108468A1910

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	0226426e-4d0b-42da-9e6f-282106dd0b76 Italy (IT)
Simplified SCIP	bf9c64ff-d6b3-4308-9da4-a169626d59b6 Germany (DE) ca801d55-6616-4987-addf-3569e15d5365 Poland (PL) d28176c0-f378-491d-a052-0bd2c5c68c68 Sweden (SE) 3f129954-20c9-4a45-bfe7-0f4a2521f367 Germany (DE) c48b8c62-2578-4968-84bf-7ac305ebe5ac Czech Republic (CZ) 315e700e-7549-4a69-8d34-8149f325439f Croatia (HR) a51b06f4-40d0-4b71-a938-8eefb09d739c Belgium (BE) fe06fb64-1e9d-4a77-80b5-f822da0f8de9 Finland (FI) 8a87e212-b122-495b-bed9-77c129a88658 France (FR) 63669766-828a-45ed-bfe6-07f5a8fa8144 Poland (PL) 59ef38dd-f05e-43d0-80a7-4037f4d73901 Norway (NO) d060d81b-653e-467c-a00e-6a71d806fea6 Hungary (HU) 5b5fa984-7b63-441d-b40c-dc5cb388fcad Estonia (EE) 77c73926-313a-45fa-887f-e43a16df8464 Denmark (DK) 022046ed-8a82-4a3d-984d-09681036276b Greece (GR) f0ed3b53-344b-4175-9fc6-e25299bf69d6 Sweden (SE) c1f569f8-0d28-48d7-95be-636e2acbbda6 Germany (DE) daac185f-7c35-4bb1-9bff-c4545f6af736 Germany (DE) f8ef2554-6ca3-4133-9b0e-ee0d21704866 France (FR) 3137ee56-02c7-4e02-824f-ed8a3b87877e Poland (PL) 1685e5c9-4fad-4e13-82d0-7151b4572f76 Netherlands (NL) c907cf46-7918-418d-ac49-92b71b78d302 Belgium (BE) c335306c-bb22-4cf5-b259-b42bb9c81489 Germany (DE) 112ac110-3e6b-4d4d-b1ae-bca9eb7389e1 Hungary (HU) 2bc99649-9af9-4707-aefa-583587a5d475 Spain (ES) c6ae947f-73b4-4052-b698-d03ee0d454ca Portugal (PT) 1d180de9-f5a2-4449-851c-56d83071f3a0 Bulgaria (BG)

Ordering

Order Code US and Canada	ZCVWERBF000A000000XX
EAN	8015644757069
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	510 mm
-------------------	--------

Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	70 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 Gross Weight	77 kg
Package Level 1 EAN	8015644757069

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 5000 cycle Ue = 500 ... 690 V 4000 cycle 20 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	100 %
Number of Poles	4
Power Loss	465 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of Icu (Ics)	100 %
Rated Current (In)	4000 A
Rated Voltage (Ur)	690 V
Rated Impulse Withstand Voltage (Uimp)	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (Ui)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics)	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Short-time Withstand Current Low Voltage (Icw)	for 1 s 100 kA for 3 s 75 kA
Rated Ultimate Short-Circuit Breaking Capacity (Icu)	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 100 kA (525 V AC) 100 kA

	(690 V AC) 100 kA
Rated Uninterrupted Current (I _u)	4000 A
Recommended Screw Driver	Main Circuit M12
Release	Ekip Touch LSiG
Release Type	EL
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E4.2
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m
Version	F
CAD Dimensional Drawing	1SDH001252R0197

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5545
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001001R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

