



PRODUCT-DETAILS

E6.2X/f 6300 Ekip G Touch LSiG 4p F HR

E6.2X/f 6300 Ekip G Touch LSiG 4p F HR



| General Information   |                                                                                                                                                                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E6.2X/f 6300 Ekip G Touch LSiG 4p F HR                                                                                                                                                                                                     |
| Product ID            | 1SDA072037R1                                                                                                                                                                                                                               |
| EAN                   | 8015644758875                                                                                                                                                                                                                              |
| Catalog Description   | E6.2X/f 6300 Ekip G Touch LSiG 4p F HR                                                                                                                                                                                                     |
| Long Description      | C.BREAKER SACE EMAX2 E6.2X/f 6300 FIXED FOUR-POLE FULL SIZE NEUTRAL WITH<br>TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/G/TOUCH-LSIG<br>R 6300 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-<br>CLOSED |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                                      |                                                             |
|-----------------------------------------------------|-------------------------------------------------------------|
| Circular Design<br>Principles Recyclability<br>Rate | Design for Closing Resource Loops - Standard EN45555 - 77 % |

|                                             |                                                     |
|---------------------------------------------|-----------------------------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                     |
| End of Life Instructions                    | 9AKK108468A2364                                     |
| Group Waste to Landfill Target              | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326                                     |

### Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1905 |
|                                         | 9AKK108468A1913 |

### Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644758875 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 1014 mm |
| Product Net Height         | 371 mm  |
| Product Net Depth / Length | 270 mm  |
| Product Net Weight         | 140 kg  |

### Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 515 mm        |
| Package Level 1 Height         | 610 mm        |
| Package Level 1 Depth / Length | 1257 mm       |
| Package Level 1 Gross Weight   | 151 kg        |
| Package Level 1 EAN            | 8015644758875 |

### Additional Information

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Current Type          | AC                                                                             |
| Electrical Durability | Ue = < 440 V 2000 cycle<br>Ue = 500 ... 690 V 2000 cycle<br>10 cycles per hour |

|                                                                                           |                                                                                                                                                                                           |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mechanical Durability                                                                     | 12000 cycle<br>60 cycles per hour                                                                                                                                                         |
| Neutral Pole Current ([% I <sub>u</sub> ])                                                | 100 %                                                                                                                                                                                     |
| Number of Poles                                                                           | 4 / f                                                                                                                                                                                     |
| Power Loss                                                                                | 767 W                                                                                                                                                                                     |
| Product Main Type                                                                         | SACE Emax 2                                                                                                                                                                               |
| Product Name                                                                              | Air Circuit Breaker                                                                                                                                                                       |
| Product Type                                                                              | Air Circuit Breaker                                                                                                                                                                       |
| Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cu</sub> (I <sub>cs</sub> ) | 100 %                                                                                                                                                                                     |
| Rated Current (I <sub>n</sub> )                                                           | 6300 A                                                                                                                                                                                    |
| Rated Voltage (U <sub>r</sub> )                                                           | 690 V                                                                                                                                                                                     |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )                                       | acc. to IEC 60947-2 12 kV                                                                                                                                                                 |
| Rated Insulation Voltage (U <sub>i</sub> )                                                | AC 1000 V                                                                                                                                                                                 |
| Rated Operational Voltage                                                                 | 690 V AC                                                                                                                                                                                  |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )                          | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(380 V AC) 100 kA<br>(400 V AC) 100 kA<br>(415 V AC) 100 kA<br>(440 V AC) 100 kA<br>(500 V AC) 100 kA<br>(660 V AC) 100 kA<br>(690 V AC) 100 kA |
| Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )                         | for 1 s 120 kA<br>for 3 s 100 kA                                                                                                                                                          |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )                         | (440 V AC) 200 kA                                                                                                                                                                         |
| Rated Uninterrupted Current (I <sub>u</sub> )                                             | 6300 A                                                                                                                                                                                    |
| Release                                                                                   | Ekip G Touch LSiG                                                                                                                                                                         |
| Release Type                                                                              | EL                                                                                                                                                                                        |
| Short-Circuit Performance Level                                                           | X                                                                                                                                                                                         |
| Standards                                                                                 | IEC                                                                                                                                                                                       |
| Sub-type                                                                                  | E6.2                                                                                                                                                                                      |
| Terminal Connection Type                                                                  | Rear flat Horizontal                                                                                                                                                                      |
| Version                                                                                   | F                                                                                                                                                                                         |

**Certificates and Declarations**

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Declaration of Conformity - CE    | 9AKK106713A5544 |
| Instructions and Manuals          | 1SDH001000R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R1002 |

| Classifications            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 4. Large Equipment (Any External Dimension More Than 50 cm)                  |
| eClass                     | V11.1 : 27370409                                                             |

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

