



PRODUCT-DETAILS

E6.2X 4000 Ekip Touch LSI 4p WMP  
E6.2X 4000 Ekip Touch LSI 4p WMP



| General Information   |                                                                                                                                                                                       |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E6.2X 4000 Ekip Touch LSI 4p WMP                                                                                                                                                      |
| Product ID            | 1SDA073235R1                                                                                                                                                                          |
| EAN                   | 8015644770853                                                                                                                                                                         |
| Catalog Description   | E6.2X 4000 Ekip Touch LSI 4p WMP                                                                                                                                                      |
| Long Description      | MOVING PART FOR C.BREAKER SACE EMAX2 E6.2X 4000 FOUR-POLE WITH SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 4000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                                    |                                                             |
|---------------------------------------------------|-------------------------------------------------------------|
| Circular Design Principles<br>Recyclability Rate  | Design for Closing Resource Loops - Standard EN45555 - 77 % |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108467A5658                                             |

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| End of Life Instructions            | 9AKK108468A2364                                     |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Environmental Product Declaration - EPD | 9AKK108468A1905<br>9AKK108468A1913 |
|-----------------------------------------|------------------------------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644770853 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 929 mm |
| Product Net Height         | 425 mm |
| Product Net Depth / Length | 383 mm |
| Product Net Weight         | 134 kg |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 515 mm        |
| Package Level 1 Height         | 610 mm        |
| Package Level 1 Depth / Length | 1127 mm       |
| Package Level 1 Gross Weight   | 143 kg        |
| Package Level 1 EAN            | 8015644770853 |

Additional Information

|                               |                                                                               |
|-------------------------------|-------------------------------------------------------------------------------|
| Current Type                  | AC                                                                            |
| Electrical Durability         | Ue =< 440 V 4000 cycle<br>Ue = 500 ... 690 V 4000 cycle<br>10 cycles per hour |
| Mechanical Durability         | 12000 cycle<br>60 cycles per hour                                             |
| Neutral Pole Current ([% Iu]) | 50 %                                                                          |
| Number of Poles               | 4                                                                             |
| Power Loss                    | 544 W                                                                         |
| Product Main Type             | SACE Emax 2                                                                   |
| Product Name                  | Air Circuit Breaker                                                           |

|                                                                               |                                                                                                                                                                                           |
|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Type                                                                  | Air Circuit Breaker                                                                                                                                                                       |
| Rated Service Short-Circuit Breaking Capacity, in % of Icu (I <sub>cs</sub> ) | 100 %                                                                                                                                                                                     |
| Rated Current (I <sub>n</sub> )                                               | 4000 A                                                                                                                                                                                    |
| Rated Voltage (U <sub>r</sub> )                                               | 690 V                                                                                                                                                                                     |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )                           | acc. to IEC 60947-2 12 kV                                                                                                                                                                 |
| Rated Insulation Voltage (U <sub>i</sub> )                                    | AC 1000 V                                                                                                                                                                                 |
| Rated Operational Voltage                                                     | 690 V AC                                                                                                                                                                                  |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )              | (220 V AC) 200 kA<br>(230 V AC) 200 kA<br>(380 V AC) 200 kA<br>(400 V AC) 200 kA<br>(415 V AC) 200 kA<br>(440 V AC) 200 kA<br>(500 V AC) 130 kA<br>(660 V AC) 120 kA<br>(690 V AC) 120 kA |
| Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )             | for 1 s 120 kA<br>for 3 s 100 kA                                                                                                                                                          |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )             | (440 V AC) 200 kA                                                                                                                                                                         |
| Rated Uninterrupted Current (I <sub>u</sub> )                                 | 4000 A                                                                                                                                                                                    |
| Release                                                                       | Ekip Touch LSI                                                                                                                                                                            |
| Release Type                                                                  | EL                                                                                                                                                                                        |
| Short-Circuit Performance Level                                               | X                                                                                                                                                                                         |
| Standards                                                                     | IEC                                                                                                                                                                                       |
| Sub-type                                                                      | E6.2                                                                                                                                                                                      |
| Version                                                                       | W                                                                                                                                                                                         |

Certificates and Declarations

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Declaration of Conformity - CE    | 9AKK106713A5544 |
| Instructions and Manuals          | 1SDH001000R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R1002 |

Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 4. Large Equipment (Any External Dimension More Than 50 cm)                  |
| eClass                     | V11.1 : 27370409                                                             |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

