



PRODUCT-DETAILS

E6.2X 6300 Ekip Dip LI 4p WMP

E6.2X 6300 Ekip Dip LI 4p WMP



General Information	
Extended Product Type	E6.2X 6300 Ekip Dip LI 4p WMP
Product ID	1SDA073291R1
EAN	8015644771416
Catalog Description	E6.2X 6300 Ekip Dip LI 4p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E6.2X 6300 FOUR-POLE WITH SOLID-STATE RELEASE IN AC Ekip/DIP-LI R 6300 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED
ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 77 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2364
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1905 9AKK108468A1913
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644771416
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	929 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	134 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1127 mm
Package Level 1 Gross Weight	143 kg
Package Level 1 EAN	8015644771416

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 2000 cycle Ue = 500 ... 690 V 2000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	50 %
Number of Poles	4
Power Loss	1550 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker

Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I _{cs})	100 %
Rated Current (I _n)	6300 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 200 kA (400 V AC) 200 kA (415 V AC) 200 kA (440 V AC) 200 kA (500 V AC) 130 kA (660 V AC) 120 kA (690 V AC) 120 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 120 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(440 V AC) 200 kA
Rated Uninterrupted Current (I _u)	6300 A
Release	Ekip Dip LI
Release Type	EL
Short-Circuit Performance Level	X
Standards	IEC
Sub-type	E6.2
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

[Low Voltage Products and Systems](#) → [Circuit Breakers](#) → [Air Circuit Breakers](#) → [Emax 2](#)

