



PRODUCT-DETAILS

E1.2N/MS 630 3p WMP

E1.2N/MS 630 3p WMP



General Information	
Extended Product Type	E1.2N/MS 630 3p WMP
Product ID	1SDA073477R1
EAN	8015644773274
Catalog Description	E1.2N/MS 630 3p WMP
Long Description	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E1.2N/MS 630 THREE-POLE

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2360
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1900
	9AKK108468A3028

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	Z1NN00A00000000000XX
EAN	8015644773274
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	278 mm
Product Net Height	363.5 mm
Product Net Depth / Length	271 mm
Product Net Weight	18 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	20 kg
Package Level 1 EAN	8015644773274

Additional Information

Current Type	AC
Electrical Durability	Ue = < 440 V 8000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour

Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	62 W
Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Rated Current (I_n)	630 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA for 3 s 30 kA
Rated Uninterrupted Current (I_u)	630 A
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E1.2
Version	W
CAD Dimensional Drawing	1SDH001252R0024

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5546
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH000999R0103
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH000999R0002

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
Object Classification Code	Q
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

