



PRODUCT-DETAILS

E2.2N/MS 1250 4p WMP

E2.2N/MS 1250 4p WMP



General Information	
Extended Product Type	E2.2N/MS 1250 4p WMP
Product ID	1SDA073529R1
EAN	8015644773793
Catalog Description	E2.2N/MS 1250 4p WMP
Long Description	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E2.2N/MS 1250 FOUR-POLE

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1902 9AKK108468A1909
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	ZBNR00A00000000000XX
EAN	8015644773793
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	407 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	55 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	60 kg
Package Level 1 EAN	8015644773793

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 15000 cycle Ue = 500 ... 690 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour

Neutral Pole Current ([% I _n])	100 %
Number of Poles	4
Power Loss	176 W
Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Rated Current (I _n)	1250 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 66 kA for 3 s 50 kA
Rated Uninterrupted Current (I _u)	1250 A
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	E2.2
Version	W
CAD Dimensional Drawing	1SDH001252R0432

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0109 1SDC200023D0209 1SDC200023D0709 1SDC200023D0309 1SDC200023D0909 1SXF200023C2001
Declaration of Conformity - CE	9AKK106713A5902
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001000R0102
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0003 1SDH001000R0002 1SDH001000R0005 1SDH001000R0004 1SDH001000R0001 1SDH001000R0006

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter

ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	5293 >> Switch disconnecter
Object Classification Code	Q
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

