



PRODUCT-DETAILS

E6.2X/f/MS 6300 4p WMP

E6.2X/f/MS 6300 4p WMP



General Information	
Extended Product Type	E6.2X/f/MS 6300 4p WMP
Product ID	1SDA073558R1
EAN	8015644774080
Catalog Description	E6.2X/f/MS 6300 4p WMP
Long Description	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E6.2X/f/MS 6300 FOUR-POLE FULL SIZE NEUTRAL

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 77 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)		
End of Life Instructions		9AKK108468A2364
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available	
Toxic Substances Control Act - TSCA		9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1905
	9AKK108468A1913

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644774080
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	1069 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	148 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1257 mm
Package Level 1 Gross Weight	159 kg
Package Level 1 EAN	8015644774080

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 2000 cycle Ue = 500 ... 690 V 2000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour

Neutral Pole Current ([% I _u])	100 %
Number of Poles	4 / f
Power Loss	1550 W
Product Main Type	SACE Emax 2
Product Name	Switch Disconnecter
Product Type	Switch Disconnecter
Rated Current (I _n)	6300 A
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 120 kA for 3 s 100 kA
Rated Uninterrupted Current (I _u)	6300 A
Short-Circuit Performance Level	X
Standards	IEC
Sub-type	E6.2
Version	W

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

