



PRODUCT-DETAILS

XT2S 125 Ekip LS/I In=10A 3p F F UL/CSA

XT2S 125 Ekip LS/I In=10A 3p F F UL/CSA



General Information

|                       |                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT2S 125 Ekip LS/I In=10A 3p F F UL/CSA                                                                             |
| Product ID            | 1SDA074910R1                                                                                                        |
| EAN                   | 8015644788872                                                                                                       |
| Catalog Description   | XT2S 125 Ekip LS/I In=10A 3p F F UL/CSA                                                                             |
| Long Description      | C.BREAKER TMAX XT2S 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 10 A |

ABB EcoSolutions

|                  |     |
|------------------|-----|
| ABB EcoSolutions | Yes |
|------------------|-----|

Circular Value

|                                             |                                                                |
|---------------------------------------------|----------------------------------------------------------------|
| Circular Design Principles                  | Design for Closing Resource Loops - Standard EN45555 - 55.70 % |
| Recyclability Rate                          |                                                                |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                |
| End of Life Instructions                    | 9AKK108468A2349                                                |

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1897 |
|-----------------------------------------|-----------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                    |
|--------------------------|--------------------|
| Order Code US and Canada | XT2SU3010EFF000XXX |
| EAN                      | 8015644788872      |
| Minimum Order Quantity   | 1 piece            |
| Customs Tariff Number    | 85362090           |

Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 90 mm   |
| Product Net Height         | 130 mm  |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight         | 1.12 kg |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 131 mm        |
| Package Level 1 Height         | 212 mm        |
| Package Level 1 Depth / Length | 147 mm        |
| Package Level 1 Gross Weight   | 1.22 kg       |
| Package Level 1 EAN            | 8015644788872 |

Additional Information

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Circuit Breaker Type to be Associated | Power Distribution                 |
| Connecting Capacity Main Circuit      | Busbar 32.5..100 mm²               |
| Current Type                          | AC                                 |
| Electrical Durability                 | 120 cycles per hour<br>8000 cycle  |
| Mechanical Durability                 | 240 cycles per hour<br>25000 cycle |
| Number of Poles                       | 3                                  |
| Opening Time                          | CB with SOR 15 ms                  |

|                                               |                                              |
|-----------------------------------------------|----------------------------------------------|
|                                               | CB with UVR 15 ms                            |
| Order Multiple                                | 1 piece                                      |
| Power Loss                                    | at Rated Operating Conditions per Pole 0.1 W |
| Product Main Type                             | SACE Tmax XT                                 |
| Product Name                                  | Moulded Case Circuit Breaker                 |
| Product Type                                  | Automatic Circuit Breaker                    |
| Rated Current (I <sub>n</sub> )               | 10 A                                         |
| Rated Voltage (U <sub>r</sub> )               | 600 V                                        |
| Rated Operational Voltage                     | 600 V AC                                     |
| Rated Uninterrupted Current (I <sub>u</sub> ) | 125 A                                        |
| Recommended Screw Driver                      | Main Circuit M6                              |
| Release                                       | Ekip LS/I                                    |
| Release Type                                  | EL                                           |
| Short-Circuit Performance Level               | S                                            |
| Standards                                     | UL489                                        |
| Sub-type                                      | XT2                                          |
| Suitable for Product Class                    | SACE Tmax XT                                 |
| Terminal Connection Type                      | Front                                        |
| Terminal Type                                 | Bolt                                         |
| Tightening Torque                             | 6 N·m                                        |
| Version                                       | F                                            |
| CAD Dimensional Drawing                       | 1SDH002230A1001                              |

Technical UL/CSA

|                                   |                                                           |
|-----------------------------------|-----------------------------------------------------------|
| Interrupting Rating acc. to UL489 | (240 V AC) 100 kA<br>(480 V AC) 35 kA<br>(600 V AC) 22 kA |
|-----------------------------------|-----------------------------------------------------------|

Certificates and Declarations

|                                   |                                    |
|-----------------------------------|------------------------------------|
| ATEX Certificate                  | No certification needed            |
| CSA Certificate (Intrinsic Safe)  | 9AKK10103A3906                     |
| Data Sheet, Technical Information | 1SDC210200D0206<br>1SDC210199D0206 |
| Declaration of Conformity - CE    | 9AKK106713A5901                    |
| UL Certificate                    | 1SDL000163R0112                    |
| VDE Certificate                   | No certification needed            |
| Dimension Diagram                 | 1SDH000721R0100                    |
| Mechanical Drawings               | 1SDH000721R0100                    |
| Wiring Diagram                    | 1SDM000068R0001                    |
| Instructions and Manuals          | 1SDH000721R0003<br>1SDH000721R0505 |

Classifications

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| ETIM 7                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers          |
| Object Classification Code         | Q                                                                            |
| UNSPSC                             | 39121616                                                                     |

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

eClass

V11.1 : 27370409

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

