



PRODUCT-DETAILS

XT2V 125 Ekip LS/I In=25A 3p F F UL/CSA

XT2V 125 Ekip LS/I In=25A 3p F F UL/CSA



General Information	
Extended Product Type	XT2V 125 Ekip LS/I In=25A 3p F F UL/CSA
Product ID	1SDA074941R1
EAN	8015644789183
Catalog Description	XT2V 125 Ekip LS/I In=25A 3p F F UL/CSA
Long Description	C.BREAKER TMAX XT2V 125 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 25 A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 55.70 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2349
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1897
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT2VU3025EFF000XXX
EAN	8015644789183
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	90 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.12 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	131 mm
Package Level 1 Height	212 mm
Package Level 1 Depth / Length	147 mm
Package Level 1 Gross Weight	1.22 kg
Package Level 1 EAN	8015644789183

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 32.5..100 mm²

Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 0.8 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	25 A
Rated Voltage (U _r)	600 V
Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I _u)	125 A
Recommended Screw Driver	Main Circuit M6
Release	Ekip LS/I
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL489
Sub-type	XT2
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m
Version	F
CAD Dimensional Drawing	1SDH002230A1001

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 200 kA (480 V AC) 150 kA (600 V AC) 42 kA
-----------------------------------	--

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3906
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of Conformity - CE	9AKK106713A5901
UL Certificate	1SDL000163R0112
VDE Certificate	No certification needed
Dimension Diagram	1SDH000721R0100
Mechanical Drawings	1SDH000721R0100

Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000721R0003
	1SDH000721R0505

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

