



PRODUCT-DETAILS

XT3N 225 TMF 125-1250 4p F F UL/CSA

XT3N 225 TMF 125-1250 4p F F UL/CSA



General Information	
Extended Product Type	XT3N 225 TMF 125-1250 4p F F UL/CSA
Product ID	1SDA075124R1
EAN	8015644791018
Catalog Description	XT3N 225 TMF 125-1250 4p F F UL/CSA
Long Description	C.BREAKER TMAX XT3N 225 UL/CSA FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 125-1250 A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 56.6 %
Conflict Minerals Reporting Template	9AKK108467A5658

(CMRT)

End of Life Instructions	9AKK108468A2350
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A2294
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	XT3NU4125AFF000XXX
EAN	8015644791018
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	150 mm
Product Net Depth / Length	70 mm
Product Net Weight	2.1 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	155 mm
Package Level 1 Height	190 mm
Package Level 1 Depth / Length	155 mm
Package Level 1 Gross Weight	2.1 kg
Package Level 1 EAN	8015644791018

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 85..192 mm²

Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	4
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 6.6 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	125 A
Rated Voltage (U _r)	600Y/347 V
Rated Instantaneous Short-Circuit Current Setting (I _i)	1250 A
Rated Operational Voltage	600Y/347 V AC 500 V DC
Rated Uninterrupted Current (I _u)	225 A
Recommended Screw Driver	Main Circuit M8
Release	TMF
Release Type	TM
Setting Range	125 A
Short-Circuit Performance Level	N
Standards	UL489
Sub-type	XT3
Suitable for Product Class	SACE Tmax XT
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	8 N·m
Version	F
CAD Dimensional Drawing	1SDH001295R0483

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA (480 V AC) 25 kA (600Y / 347 V AC) 10 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 3 Poles in Series 25 kA
-----------------------------------	---

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	9AKK10103A3907
Data Sheet, Technical Information	1SDC210200D0206 1SDC210199D0206
Declaration of	9AKK106713A5530

Conformity - CE	
UL Certificate	1SDL000163R0113
VDE Certificate	No certification needed
Dimension Diagram	1SDH000720R0100
Mechanical Drawings	1SDH000720R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000720R0003

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4927 >> Molded case circuit breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

