



PRODUCT-DETAILS

E1.2B-A 800 Ekip Dip LSIG 3p F F

E1.2B-A 800 Ekip Dip LSIG 3p F F



General Information	
Extended Product Type	E1.2B-A 800 Ekip Dip LSIG 3p F F
Product ID	1SDA076910R1
EAN	8015644833336
Catalog Description	E1.2B-A 800 Ekip Dip LSIG 3p F F
Long Description	C.BREAKER SACE EMAX2 E1.2B-A 800 UL FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2360
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1901
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	4d72bbdc-4498-43ca-b3e7-524a2bc4f69f Italy (IT)
Simplified SCIP	b7670ca7-f20d-4eb1-b067-545d516986db Germany (DE) 137a2f81-207b-4507-a8e5-b9267e68033f Portugal (PT) 87677ba1-77f0-4505-9413-d5f78b82fb80 Bulgaria (BG) c480aec3-ba83-4a3b-9c36-a1ea2124f98f Sweden (SE) e3099993-e7b1-493f-b38e-26d91e5e24b1 Poland (PL) e6ac4acf-af2a-4e19-b6ba-e334345c2438 Hungary (HU) 207b2f56-c840-4fbb-a6e4-172b8487ed23 Germany (DE) 26615a77-bbf2-4a8a-9609-3f3474cfab79 Denmark (DK) b6274a03-9d67-4e8d-bf5c-761c8945ebf3 Norway (NO) 52d52c73-2212-4b94-a9a8-51138efaa1ef Poland (PL) 2fd02f24-6b9a-4ae3-a3db-38e086b75199 Sweden (SE) ab294489-9cad-4701-ab61-357201050f05 Belgium (BE) 464da90f-814a-4f99-b259-63c2cfd34bc Finland (FI) f5e36522-d27b-4266-91da-da164dc62026 Croatia (HR) cbe710f8-99fc-4a52-b47b-b986afbcaf54 France (FR) 14d99011-6491-489c-8fdf-2a179c63758d Germany (DE) 8ea2850b-bc7b-4886-9f66-2685c4180cde Czech Republic (CZ) 888e4b8b-40b6-4163-b040-24cc2735082c Poland (PL) fa36058d-e0be-4183-addb-7683d0b7506f Germany (DE) 882b987b-5244-4121-9a0e-ee1fde34cc3e Germany (DE) c996fd89-fe73-4f99-ac50-a8fd476c256f Spain (ES) c3cfd06b-4c8a-46d3-a286-a8c0546ab744 Hungary (HU) 094d6648-028c-4588-9516-c0b8b4ef19d4 France (FR) bbdcf65f-1f3b-4382-bc3d-c195dd6e56da Netherlands (NL) 0c90595b-aed6-4881-8f24-752a470022f2 Belgium (BE) e65bc877-e6fa-4c09-b1fc-d29b391400d6 Greece (GR) b854c5ff-4eed-43fd-acd1-bf47f178a00e Estonia (EE)

Ordering

Order Code US and Canada	Z1BCUFBC000A000000XX
EAN	8015644833336
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	214 mm
-------------------	--------

Product Net Height	295 mm
Product Net Depth / Length	184 mm
Product Net Weight	11 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	365 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	16 kg
Package Level 1 EAN	8015644833336

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 59 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	800 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	B
Standards	UL
Sub-type	E1.2
Terminal Connection Type	Front
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
-----------------------------------	-----------------

Declaration of Conformity - CE	9AKK106713A5546
Instructions and Manuals	1SDH000999R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

