



PRODUCT-DETAILS

E1.2S-A 1200 Ekip Touch LSI 3p F F

E1.2S-A 1200 Ekip Touch LSI 3p F F



| General Information   |                                                                                                                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E1.2S-A 1200 Ekip Touch LSI 3p F F                                                                                                                                                                    |
| Product ID            | 1SDA076982R1                                                                                                                                                                                          |
| EAN                   | 8015644834050                                                                                                                                                                                         |
| Catalog Description   | E1.2S-A 1200 Ekip Touch LSI 3p F F                                                                                                                                                                    |
| Long Description      | C.BREAKER SACE EMAX2 E1.2S-A 1200 UL FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

| ABB EcoSolutions |     |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value                |                                                               |
|-------------------------------|---------------------------------------------------------------|
| Circular Design               | Design for Closing Resource Loops - Standard EN45555 - 76.4 % |
| Principles Recyclability Rate |                                                               |
| Conflict Minerals             | 9AKK108467A5658                                               |

Reporting Template  
(CMRT)

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| End of Life Instructions            | 9AKK108468A2360                                     |
| Group Waste to Landfill Target      | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326                                     |

Eco Transparency

|                                         |                 |
|-----------------------------------------|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1901 |
|-----------------------------------------|-----------------|

Environmental

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Environmental Information | 9AKK108467A6707                                                        |
| REACH Declaration         | 9AKK108466A1425                                                        |
| RoHS Information          | 9AKK108466A1424                                                        |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

|                          |                      |
|--------------------------|----------------------|
| Order Code US and Canada | Z1SDUHBEO00A000000XX |
| EAN                      | 8015644834050        |
| Minimum Order Quantity   | 1 piece              |
| Customs Tariff Number    | 85362090             |

Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 214 mm |
| Product Net Height         | 295 mm |
| Product Net Depth / Length | 184 mm |
| Product Net Weight         | 11 kg  |

Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 365 mm        |
| Package Level 1 Height         | 350 mm        |
| Package Level 1 Depth / Length | 330 mm        |
| Package Level 1 Gross Weight   | 16 kg         |
| Package Level 1 EAN            | 8015644834050 |

Additional Information

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Current Type          | AC                                                      |
| Electrical Durability | Ue =< 508 V 7000 cycle<br>Ue = 508 ... 635 V 6500 cycle |

|                                            |                                              |
|--------------------------------------------|----------------------------------------------|
|                                            | 30 cycles per hour                           |
| Mechanical Durability                      | 20000 cycle                                  |
|                                            | 60 cycles per hour                           |
| Number of Poles                            | 3                                            |
| Power Loss                                 | at Rated Operating Conditions per Pole 125 W |
| Product Main Type                          | SACE Emax 2                                  |
| Product Name                               | Air Circuit Breaker                          |
| Product Type                               | Air Circuit Breaker                          |
| Rated Current (I <sub>N</sub> )            | 1200 A                                       |
| Rated Voltage (U <sub>r</sub> )            | 600 V                                        |
| Rated Insulation Voltage (U <sub>i</sub> ) | AC 635 V                                     |
| Rated Operational Voltage                  | 600 V AC                                     |
| Release                                    | Ekip Touch LSI                               |
| Release Type                               | EL                                           |
| Short-Circuit Performance Level            | S                                            |
| Standards                                  | UL                                           |
| Sub-type                                   | E1.2                                         |
| Terminal Connection Type                   | Front                                        |
| Version                                    | F                                            |

**Technical UL/CSA**

|                                    |               |
|------------------------------------|---------------|
| Interrupting Rating acc. to UL1066 | (254 V) 65 kA |
|                                    | (508 V) 65 kA |
|                                    | (635 V) 42 kA |

**Certificates and Declarations**

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SXU200040C0201 |
| Declaration of Conformity - CE    | 9AKK106713A5546 |
| Instructions and Manuals          | 1SDH000999R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R1002 |

**Classifications**

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| ETIM 7                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                             | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers                                                 |
| UNSPSC                             | 39121615                                                                     |
| WEEE Category                      | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                             | V11.1 : 27370409                                                             |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

