



PRODUCT-DETAILS

E1.2B-A 1200 Ekip Touch LSI 3p WMP

E1.2B-A 1200 Ekip Touch LSI 3p WMP



General Information	
Extended Product Type	E1.2B-A 1200 Ekip Touch LSI 3p WMP
Product ID	1SDA077082R1
EAN	8015644835057
Catalog Description	E1.2B-A 1200 Ekip Touch LSI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2B-A 1200 UL THREE-POLE WITH SOLID -STATE RELEASE IN AC EKIP/TOUCH-LSI R 1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2360
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1901
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	20d923dd-0f37-441a-a895-f60e6553e3d1 Italy (IT)
Simplified SCIP	d1c4e794-871c-4b0e-8abe-00fcb8bed57d Hungary (HU) c9a5cb39-a830-4f2a-ac05-c677794a7acd Finland (FI) 4c3abda3-93f5-438d-a699-a6f551d10792 Belgium (BE) 3e3436d5-bdd2-45bc-a13f-937da344c79a Croatia (HR) 72578792-278f-4528-9632-c596f93a373b Poland (PL) d0de3ab4-2887-4ddc-8120-0ad29d48d897 Germany (DE) c6fade80-5fd0-4122-98d5-921f1062178b Germany (DE) ee200d1b-9f15-4c20-8c46-9e580a18006b Sweden (SE) 95f71834-b76e-4dd8-8ad2-67dbf3916994 Poland (PL) 741259b1-f8c8-481e-a907-51a5749c3bee Czech Republic (CZ) 40cb9bef-cad8-4026-9bd5-c56e0eb14e7c Norway (NO) c670cbf5-ee14-46dc-b070-ad1cf362141e Portugal (PT) c07a487d-e201-47b1-ac7d-6357183a726c Denmark (DK) 1f676865-5248-42d7-a1b9-96eeb19cd2b8 Germany (DE) 44788905-bcc9-48be-bd24-4cc1133dd97f Estonia (EE) 9b622654-adc8-4da1-8d57-657baf7a9bf3 Bulgaria (BG) 183a9052-1ec9-40b6-9eae-8486c987e43a Poland (PL) b693adf1-aa74-4149-85e1-aebec6827d94 France (FR) 04c6f516-23f1-4b4e-b650-c1baaef6edb9 Sweden (SE) f64d935e-48c3-49e2-a938-95222adb7a6a Germany (DE) e1ecb6af-34e9-4308-9d79-a8cbe0b66e6c Netherlands (NL) 7fcc3e86-98a2-4895-bdde-b4d6941ce170 Greece (GR) 31c3c3db-6f34-4056-8cd7-37582357311e Germany (DE) 71f77a3f-04be-4547-9093-c76050cdef97 Belgium (BE) 70803cd8-de83-4208-ba48-768cc51a9565 Hungary (HU) 919afd1f-401d-4ada-9a2d-41b0ccfc7abc France (FR) b7ee603c-d75e-40a1-bab2-e62668a56e6c Spain (ES)

Ordering

Order Code US and Canada	Z1BDUHAE000A000000XX
EAN	8015644835057
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	278 mm
-------------------	--------

Product Net Height	363.5 mm
Product Net Depth / Length	281 mm
Product Net Weight	14 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	365 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	22 kg
Package Level 1 EAN	8015644835057

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 250 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSI
Release Type	EL
Short-Circuit Performance Level	B
Standards	UL
Sub-type	E1.2
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 42 kA (508 V) 42 kA (635 V) 42 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5546

Instructions and Manuals	1SDH000999R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

