



PRODUCT-DETAILS

E1.2S-A 250 Ekip Touch LSI 3p WMP

E1.2S-A 250 Ekip Touch LSI 3p WMP



General Information

Extended Product Type	E1.2S-A 250 Ekip Touch LSI 3p WMP
Product ID	1SDA077112R1
EAN	8015644835354
Catalog Description	E1.2S-A 250 Ekip Touch LSI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2S-A 250 UL THREE-POLE WITH SOLID-STATE RELEASE IN AC Ekip/TOUCH-LSI R 250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

End of Life Instructions	9AKK108468A2360
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1901
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	77c410c1-1c40-40d5-92ba-f1522f6d1632 Italy (IT)
Simplified SCIP	a3682502-2f91-4fd0-99fa-cf2ada4963dd Hungary (HU) c15d8ffa-105e-4695-88bf-7456aaa5bd45 Germany (DE) 0ca2efd9-e5dd-4c6b-b5ea-218c9b48889f Poland (PL) 4642bfab-e8f1-4e4b-8bb7-5c1b9857b715 Belgium (BE) 1966df21-17a1-41b4-9375-f499f5041761 Croatia (HR) dc71a7ea-7d1c-4c5a-abb9-c75644210d42 Germany (DE) 04257268-282a-4a86-a15b-667610ab6a96 Finland (FI) a18e7200-f347-416d-9731-6888cdcd80a1 France (FR) aeb03f43-23e3-4598-b791-ef854c2c0b65 Belgium (BE) 86cf1b82-6852-44aa-984f-f5e9b829d1b7 Hungary (HU) 84b114e6-5cac-450f-91c6-ff168ae6147a Spain (ES) 001f3250-2f95-465a-8f62-ba3cfee29553 Germany (DE) c109d617-f6e6-49f8-b73e-4647406f1643 Portugal (PT) 404f4924-996c-44ac-8b79-b59f90ebcaaa Denmark (DK) 73551d89-e79e-46e0-8720-1bdc1a26e505 Norway (NO) df9b1b63-43aa-4951-8658-80787c1e7dfa Czech Republic (CZ) 8c8fa362-8160-4af7-bbaa-742493d388c9 Germany (DE) 83a6371b-9fb9-425b-9620-1c3cd95d7602 Greece (GR) 488af65e-8ed2-4816-a6ff-bb3a59cbc2b0 Netherlands (NL) 9e69f5cf-6561-472a-9a34-031676592615 Sweden (SE) dbcec6e9-4d47-44aa-9c95-c8526935ba45 Poland (PL) 20229e64-cdd8-4cd0-8103-9abc27fbed75 Sweden (SE) 482f0783-4a3c-4b8a-9dd7-747f28d1cf63 France (FR) ccd7cad0-93d4-4f67-9dd1-04c013232d52 Poland (PL) 78fec8dc-f3a7-46fa-b2cd-453345205933 Estonia (EE) 66d316a1-5159-403a-93e1-62339215b05e Bulgaria (BG) a9343c46-7e25-4adf-9058-bbead75a7734 Germany (DE)

Ordering

Order Code US and Canada	Z1SAUCAE000A000000XX
EAN	8015644835354
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	278 mm
Product Net Height	363.5 mm
Product Net Depth / Length	281 mm
Product Net Weight	14 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	365 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	330 mm
Package Level 1 Gross Weight	22 kg
Package Level 1 EAN	8015644835354

Additional Information	
Current Type	AC
Electrical Durability	Ue =< 508 V 8000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 14 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	250 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL
Sub-type	E1.2
Version	W

Technical UL/CSA	
Interrupting Rating acc. to UL1066	(254 V) 65 kA (508 V) 65 kA (635 V) 42 kA

Certificates and Declarations	
Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5546
Instructions and Manuals	1SDH000999R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications	
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category	4926 >> Air circuit breakers

Code (IGCC)	
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

