



PRODUCT-DETAILS

E2.2H-A 2000 Ekip Touch LSI 3p F HR

E2.2H-A 2000 Ekip Touch LSI 3p F HR



General Information	
Extended Product Type	E2.2H-A 2000 Ekip Touch LSI 3p F HR
Product ID	1SDA077272R1
EAN	8015644836955
Catalog Description	E2.2H-A 2000 Ekip Touch LSI 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2H-A 2000 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	d1025f47-ca18-4914-b427-077e1c286af3 Italy (IT)
Simplified SCIP	1f860407-c8b1-4982-8587-6c4b19d55567 Germany (DE) 3a73d65e-c5e0-4d4e-b399-caa42eb61016 Hungary (HU) 09f50db3-f21e-4940-b8d5-56bf2a083a80 Czech Republic (CZ) c925a71c-0422-4bb6-8cbd-e5088e1448a2 Norway (NO) 8a38e0f3-f0e8-463a-ab24-1033ce0ed59c Poland (PL) 88b74e78-f749-403d-b3f0-785c26208cb1 Poland (PL) aac8a8e9-a60f-42c4-a815-e39681d6dd06 France (FR) 22d18891-9ad2-48bb-b583-d4dcd428ff29 Finland (FI) 1ac9eb66-c96f-4081-b969-ef3deec2202 Estonia (EE) 465180ed-c585-426d-93b1-9512a73f3863 Belgium (BE) f719f7d3-5ad4-4cb8-b675-2f71ba7e2b16 Sweden (SE) 35345455-df6b-4011-9916-df3ac1938605 Germany (DE) 9fd9123c-8acb-4830-8152-bc32d8dfaa84 Denmark (DK) f1b92f9f-552c-49aa-86c8-2ba55865e0d8 Germany (DE) e4e5fe13-7f07-4fd1-9b28-fcf8a0c130e1 Germany (DE) 04d3840b-41ab-4dbc-b90a-018be2e0461f Germany (DE) aabde1c2-2c06-403f-9a95-5cd99dd489ce Greece (GR) e12f4f2c-6024-40de-bdc1-9ff6f73aaf73 France (FR) fb7c7787-e173-402c-b8d2-0f78e3bc61b9 Croatia (HR) 7baae0ae-8dcc-408d-879e-483b8d3a1aab Hungary (HU) 9ed004be-48f3-406f-924b-b17d53e4ae45 Spain (ES) 7d4a0dd6-4e5a-4b64-b555-6c4f34f5ecf4 Belgium (BE) aedfd268-07a4-4b55-b94a-eeeef54e32f0 Netherlands (NL) 32e0c4bf-f38c-4982-bcf5-8906d52f5566 Poland (PL) a2dc352f-84f6-4aeb-a23f-c8584f23f8ae Bulgaria (BG) b765aeed-fecf-4952-9aba-2574791b66aa Sweden (SE) fbc566f3-df3f-49f8-ad58-ff9cdc9d4576 Portugal (PT)

Ordering

Order Code US and Canada	Z2HFUKBE000A000000XX
EAN	8015644836955
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
-------------------	--------

Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	45 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	50 kg
Package Level 1 EAN	8015644836955

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 250 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSI
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
-----------------------------------	-----------------

Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

