



PRODUCT-DETAILS

E2.2V-A 250 Ekip Touch LSI 3p F HR

E2.2V-A 250 Ekip Touch LSI 3p F HR



General Information	
Extended Product Type	E2.2V-A 250 Ekip Touch LSI 3p F HR
Product ID	1SDA077342R1
EAN	8015644837655
Catalog Description	E2.2V-A 250 Ekip Touch LSI 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2V-A 250 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	dbba4768-ddaa-4739-92b7-7ac30e7e5920 Italy (IT)
Simplified SCIP	cd468e85-98f3-402a-acb0-332a56968248 Germany (DE) 145d218e-c3ca-4ab7-9647-a2c666f82392 Sweden (SE) d8610b89-6aae-41a5-b53c-890714a84c80 Finland (FI) 74b99eb1-5c69-495b-a880-3a8afd14fc30 Belgium (BE) 96ffb428-13fb-4326-bb8e-8871786d337c Czech Republic (CZ) 61c1cc6c-1d6a-4f68-b17c-b4ce4c43f303 Estonia (EE) cc87ce64-e901-45dd-91be-98679fa3af68 Greece (GR) bc4a169c-2689-4a36-8e70-df5be8e24129 Portugal (PT) 7d067424-8855-49f3-8ef1-adb98ccc4b6e Bulgaria (BG) 530c895b-ee7e-4b02-a975-84da57a87aa5 Denmark (DK) a74ffcc6-1242-4c6e-bc4d-9f2b98344030 Poland (PL) 880eac30-beca-4b9f-9607-aca283675d1b Sweden (SE) 8e27c176-f2c6-494f-95db-2f67e347b75a Hungary (HU) 267fa2bb-ab00-4282-839d-4e3ebae071d6 Croatia (HR) 6f81c5fb-b8fd-4700-8860-fc4a8c008eee Norway (NO) 7d051834-a45a-41b8-9ff9-bf7521ead716 France (FR) 4555f7de-04ef-4f84-b970-aa4845d0cbab Germany (DE) af308203-0e52-45da-b44b-0a6edb37e496 Poland (PL) 92f09d2f-4d06-4b79-af74-26fb0812251c Spain (ES) 1a42c3ab-9283-49cc-96a9-c9625e144b48 Belgium (BE) 23a57be0-e247-4845-ac40-c3244ba60d56 Germany (DE) 63ebbb9d-5cec-4905-9251-289bb0919db3 Germany (DE) d915a43c-d00e-4cef-bcc2-b07f69c35f7a Germany (DE) e60c7fd8-00ed-4429-87c3-879200549bca Poland (PL) f94eb316-4092-42f4-8acc-a4d55aecd29e France (FR) 0441e794-4b2c-456b-9d1e-3762f1d1edbf Netherlands (NL) 3d913ecf-b9ac-47e3-8469-9c41abfaef28 Hungary (HU)

Ordering

Order Code US and Canada	Z2VAUCBE000A000000XX
EAN	8015644837655
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
Product Net Height	371 mm

Product Net Depth / Length	270 mm
Product Net Weight	45 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	50 kg
Package Level 1 EAN	8015644837655

Additional Information

Current Type	AC
Electrical Durability	Ue = < 508 V 15000 cycle Ue = 508 ... 635 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	250 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SDC200023D0104 1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902

VDE Certificate	No certification needed
Instructions and Manuals	1SDH001000R0003
	1SDH001000R0002
	1SDH001000R0005
	1SDH001000R0004
	1SDH001000R0001
	1SDH001000R0006
Instructions and Manuals (Part 2)	1SDH001316R1003
	1SDH001316R1002
	1SDH001316R1005
	1SDH001316R1004
	1SDH001316R1001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

