



PRODUCT-DETAILS

E2.2V-A 250 Ekip Touch LSIG 3p F HR

E2.2V-A 250 Ekip Touch LSIG 3p F HR



General Information	
Extended Product Type	E2.2V-A 250 Ekip Touch LSIG 3p F HR
Product ID	1SDA077343R1
EAN	8015644837662
Catalog Description	E2.2V-A 250 Ekip Touch LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2V-A 250 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 250 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	Odf7b7fa-a076-415b-a0b9-5f4184320424 Italy (IT)
Simplified SCIP	c892ce8a-f9ef-4a2d-b176-d3c3011fa762 Germany (DE) aebafe6f-246f-413f-802b-c83276428c12 Bulgaria (BG) 71b3eae9-7324-4ec7-bcb2-8b58a1a90031 Greece (GR) 511aba4f-ab66-4191-a8f6-59d8020e2095 Estonia (EE) 80e15d25-2b76-4c95-b05e-7c81e0ad5788 Hungary (HU) 41f9cb25-024f-42b0-8061-f734d4bbbd35 Sweden (SE) ac0ed330-e5d2-4dd6-87df-a13d68cdc318 France (FR) 080b0e9d-1065-41a1-a9c1-0fbf37884c01 Poland (PL) 8a08f14f-22ce-40d9-9f23-d45e9bb7a6d1 Croatia (HR) 98a0e04b-af6d-445f-88fe-e6da5aa22251 Norway (NO) 596ae302-cdcd-4d78-85b9-82c08493932b Germany (DE) 1631afd4-d646-4611-8269-80901522532e Poland (PL) 7177c1fa-9695-4f25-b074-cac6315a66fd Belgium (BE) 4e659b0c-4d74-4718-bf4b-4e9bc50ab428 Spain (ES) d3ddb430-ea73-4272-a2b1-436424cf46e6 Hungary (HU) 326c23b3-5474-4830-a42b-96dcf1d8a58b Germany (DE) 42acd907-c103-4442-9779-e9df1b129ec4 Germany (DE) c83dab95-7fdf-40b6-9d3d-0a379796cff2 France (FR) 901e664b-eec5-4ff9-b493-0abf2fc11269 Poland (PL) a9d7e13d-3550-48b9-9b68-a07a5a42edf0 Netherlands (NL) 1f68fb80-81fc-40b8-8844-5eb1371e9419 Germany (DE) 35f831a0-1c05-4d5c-bba4-6c14fe9c8be8 Czech Republic (CZ) 661a52d3-247e-4064-813d-4e4e26b39ead Belgium (BE) ee9b2d59-6526-4c12-aa37-6d3aac8d73b5 Sweden (SE) 28e55458-85ca-4b62-87d7-77155cc1d01d Finland (FI) 0f9e7bd8-f81f-4a39-97b8-fd8de0afc509 Portugal (PT) 74abdf2c-7d99-4792-a2a9-7408a45c67cf Denmark (DK)

Ordering

Order Code US and Canada	Z2VAUCBF000A000000XX
EAN	8015644837662
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
-------------------	--------

Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	45 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	50 kg
Package Level 1 EAN	8015644837662

Additional Information

Current Type	AC
Electrical Durability	Ue = < 508 V 15000 cycle Ue = 508 ... 635 V 15000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	250 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of	9AKK106713A5902

Conformity - CE	
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

