



PRODUCT-DETAILS

E2.2V-A 2000 Ekip Dip LI 3p F HR

E2.2V-A 2000 Ekip Dip LI 3p F HR



General Information	
Extended Product Type	E2.2V-A 2000 Ekip Dip LI 3p F HR
Product ID	1SDA077388R1
EAN	8015644838119
Catalog Description	E2.2V-A 2000 Ekip Dip LI 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2V-A 2000 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC Ekip/DIP-LI R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	6903e138-2cee-4374-bc4d-e8d621204c55 Italy (IT)
Simplified SCIP	54d1d71e-0c6c-4f0e-8ebb-989394a460da Germany (DE) 03cc7e51-cdf9-437b-98f3-56247c5be379 Poland (PL) b1b39cca-4123-4c06-bb61-abf6e76867bb Czech Republic (CZ) 2dd8abd9-d7c7-496f-9264-23bcb35580f7 Hungary (HU) a8316224-b5b4-43a7-85f0-71872592eb37 Belgium (BE) d985966a-cf50-4dd3-a7af-d263739a442a Hungary (HU) bed37722-b594-4217-9ff3-5e0b9e6a2468 France (FR) 460ee463-a477-4868-a0e3-15d7c8b230ff Croatia (HR) d6090141-5505-4c8c-b8ff-ea9d2549b945 Germany (DE) 82518a75-fc3e-4a02-b594-3cca0ee81cf1 Denmark (DK) c9d689d4-41e5-41eb-a312-50c2776cca5e Germany (DE) 8d56e816-acde-466d-95f6-b7b786d41a40 Germany (DE) 041ed81d-2fab-4c1a-97d2-79395dee40b3 Belgium (BE) f2b262c4-19ec-4dcb-a052-5fde36c14417 Sweden (SE) 095b0492-f561-433f-94a0-74d9641ed010 Germany (DE) 81e95fd9-2385-46cd-b71a-9f87f17aed86 Estonia (EE) 8cd4cdf0-c96f-418a-8345-2320a33f1b95 Finland (FI) 2c282c5c-13b3-4040-a74a-17a610f52688 France (FR) 12bc7e7d-e804-436f-95ac-909ab4fd7f68 Poland (PL) bf29bb0d-cfa9-4579-8420-639556ae4db1 Norway (NO) db364411-1873-45f4-aaf9-e39cba364f1e Greece (GR) 18a589af-beae-47ad-9c7f-e187608de055 Portugal (PT) c2043714-d5ef-4b7f-8dc0-04df4417eee6 Sweden (SE) a294f99c-08ee-48b0-bb41-46bf6168e317 Bulgaria (BG) 9a4d9aeb-df6c-4b0c-82cf-d539d94b7113 Poland (PL) 85cb806f-dd3e-45cf-a8b1-ee5d1d2c860f Netherlands (NL) e24fcd87-cc2b-427e-bf05-9954957f2915 Spain (ES)

Ordering

Order Code US and Canada	Z2VFUKBA000A000000XX
EAN	8015644838119
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	276 mm
-------------------	--------

Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	45 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	50 kg
Package Level 1 EAN	8015644838119

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 250 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Dip LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
-----------------------------------	-----------------

Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

