



PRODUCT-DETAILS

E2.2S-A 1200 Ekip Hi-Touch LSI 4p F HR

E2.2S-A 1200 Ekip Hi-Touch LSI 4p F HR



General Information	
Extended Product Type	E2.2S-A 1200 Ekip Hi-Touch LSI 4p F HR
Product ID	1SDA077485R1
EAN	8015644839086
Catalog Description	E2.2S-A 1200 Ekip Hi-Touch LSI 4p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2S-A 1200 UL FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSI R 1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

Order Code US and Canada	ZBSDUHBJ200A000000XX
EAN	8015644839086
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	366 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	45 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	63 kg
Package Level 1 EAN	8015644839086

Additional Information

Current Type	AC
Electrical Durability	Ue = < 508 V 15000 cycle Ue = 508 ... 635 V 15000 cycle

	30 cycles per hour
Mechanical Durability	25000 cycle
	60 cycles per hour
Neutral Pole Current ([% I _n])	100 %
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 100 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	1200 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Hi-Touch LSI
Release Type	EL
Short-Circuit Performance Level	S
Standards	UL
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 65 kA (508 V) 65 kA (635 V) 65 kA
---------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

