



PRODUCT-DETAILS

E2.2H-A 2000 Ekip Touch LSIG 3p WMP

E2.2H-A 2000 Ekip Touch LSIG 3p WMP



General Information	
Extended Product Type	E2.2H-A 2000 Ekip Touch LSIG 3p WMP
Product ID	1SDA077613R1
EAN	8015644840365
Catalog Description	E2.2H-A 2000 Ekip Touch LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E2.2H-A 2000 UL THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSIG R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
Principles Recyclability Rate	
Conflict Minerals	9AKK108467A5658

Reporting Template (CMRT)	
End of Life Instructions	9AKK108468A2361
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1906
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	3013fc29-3256-4e30-8c25-5a68ec259319 Italy (IT)
Simplified SCIP	13ed3de7-ae69-4554-894d-f422b0bb25b2 Germany (DE) 7ca48736-782d-4c5b-9aaa-314edb5b323d Greece (GR) e3e4c796-72db-40eb-9ea5-13add83c7087 Portugal (PT) 0d199e9b-166f-4d49-82f6-f1a102f023a5 Bulgaria (BG) 5eb0a730-8776-4ad1-a297-cbe5d07ec128 Poland (PL) c5792a9a-b4a0-4c44-8e5e-8c5703633515 Norway (NO) 72e2856d-8e07-4c99-a0d7-a531dfebbe76 Hungary (HU) b68c97b7-bdb1-46d6-8e7c-160c8b37daea Poland (PL) 631ecb6f-2489-4939-8028-ca8779c04a59 Estonia (EE) 0ce5de6a-4694-4ed7-9d5e-9ef6c522db0e Finland (FI) ef593869-3551-4b0a-8185-a4361e01d106 France (FR) 267047e9-ec24-4e5d-8f83-28039a9c648f Germany (DE) 1f23ca9f-9dd9-4081-a573-e7600a3c9565 Belgium (BE) 780bb9a8-4eac-4aae-b6d9-d0d57bab86cd Sweden (SE) b62e8b35-5b56-4db4-b9a1-d0e41d621325 Germany (DE) 334ae0fa-e6a7-4164-8022-03c88dd788f6 Denmark (DK) c9877b7a-8e1c-47fa-8940-26e318009c55 Germany (DE) 621873bb-20c0-4826-a007-6e7fb0145456 Germany (DE) 5798b90c-fafa-487c-9452-02f42025be15 Spain (ES) e717589c-1fe6-4713-8924-45d278c70f31 Hungary (HU) 9947594e-e808-4db5-a9a8-41af7bff2d2c Poland (PL) 1c4c6781-591c-4d9d-be1a-159de547da82 Sweden (SE) 90649dc4-586e-4066-9744-c0546748d1b8 Belgium (BE) 43f79447-d812-48ab-9fe5-f879a86a4ef3 France (FR) ebcac5aa-0153-4eca-b4c5-96f4a938c135 Croatia (HR) 65b80455-a486-4b4a-a56c-ef0d7df126cf Netherlands (NL) ec74b2d0-734d-4e5a-820d-74b109324930 Czech Republic (CZ)

Ordering

Order Code US and Canada	Z2HFUKAF000A000000XX
EAN	8015644840365
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	317 mm
-------------------	--------

Product Net Height	425 mm
Product Net Depth / Length	393 mm
Product Net Weight	49 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	59 kg
Package Level 1 EAN	8015644840365

Additional Information

Current Type	AC
Electrical Durability	Ue =< 508 V 10000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 350 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I _n)	2000 A
Rated Voltage (U _r)	600 V
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Release	Ekip Touch LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	UL
Sub-type	E2.2
Version	W

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 85 kA (508 V) 85 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902

Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

